



PREMIER NUBBY Panels with *CLIMAPLUS* Performance/  
DONN CENTRICITEE DXT Suspension System

**LEED Credits**

Recycled Content: 29% – 32%  
*CLIMAPLUS* No-Sag Warranty

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials <sup>1</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
	●	●			●	●

**Features and Benefits**

- High-quality nubby cloth facing offers consistent, fine-textured appearance.
- Excellent noise reduction with NRC of .85 or .90 meets the demanding sound control needs of open-plan spaces.
- *CLIMAPLUS*™ 30-year system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a DONN® brand suspension system.
- Lightweight fiberglass basemat makes installation fast and easy.

**Applications**

- Conference rooms and executive areas
- Gymnasiums and auditoriums
- Open office plans
- Retail stores

**Substrate**

- Fiberglass

Call 888 874.2450 for samples
















White

Fine-textured panel



**30**  
 Year System Warranty  
 - No visible sag  
 - Mold/mildew protection



**PREMIER NUBBY**  
**CLIMAPLUS** Panels

Edge	Panel Size	Class	Item No.	UL Classified		LR <sup>2</sup>	Color	Grid Options	Anti-Mold & Mildew	Recycled Content <sup>3</sup>	Panel Cost
				NRC	CAC Min.						
											
SQ	2'x2'x3/4"	Class A	<b>7000G</b>	.85	—	.87	White	A, B		29%	<b>\$\$\$</b>
	2'x2'x1"	Class A	<b>7002G</b>	.90	—	.87	White	A, B		32%	<b>\$\$\$</b>
	2'x2'x1" Foil-Back	Class A	<b>7012G</b>	.90	25	.87	White	A, B		32%	<b>\$\$\$</b>
	2'x4'x1"	Class A	<b>7003G</b>	.90	—	.87	White	A, B		32%	<b>\$\$\$</b>
	2'x4'x1" Foil-Back	Class A	<b>7013G</b>	.90	25	.87	White	A, B		32%	<b>\$\$\$</b>

**Legend**

 **CLIMAPLUS Inherent Performance<sup>4</sup>**

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

A DX®/DXL™	B DXW™
	

**Grid Profile Options**

**Physical Data/  
Footnotes**

**Product literature**  
 Data sheet: SC1839

**ASTM E1264 classification**  
 Type XII, Form 2, Pattern E

**ASTM E84 surface burning characteristics**

Class A  
 Flame spread: 25  
 Smoke developed: 50

**Weight**  
 .38-.50 lb./sq. ft.

**Minimum AC**

170 for item #7003G.  
 190 for item #7013G.

**Thermal resistance**

R-3.3 (3/4" panels)  
 R-4.4 (1" panels)

**Maximum backloading**

See Warranty for details.

**Maintenance**

Can be cleaned easily with a soft brush or vacuum.

**Footnotes**

1. Dependent on location; see Sustainability selector.
2. LR values are shown as averages.
3. For details, see Sustainability selector.
4. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPLUS Ceilings Certification of Performance* (SC2451).