














**Features and Benefits**

- Fine textured cast product with durable surface that resists scrapes caused by accessing the ceiling plenum.
- Integral color masks nicks and scratches to enhance lifelong panel appearance.
- Optional FIRECODE™ formulation designed to meet life safety codes.
- Nearly two times more impact resistant than typical fine textured ceiling panels. (ASTM C367 – 2" ball hardness test).






**Applications**

- Conference and lobby areas
- Entertainment and gaming
- Executive offices
- Hotels and restaurants
- Retail stores
- Education environments
- Transportation terminals

 UL Classified

	Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR <sup>1</sup>	Color	Grid Options	Recycled Content <sup>2</sup>	Cost
Frost™ Panels	(SLB) 	2' x2' x3/4"	Class A	440	.70 	40 	.82	White	A	67%	\$\$
		2' x2' x3/4"		415	.55 	35 	.82	White	A	67%	\$\$
		2' x4' x3/4"	Class A	450	.70 	38 	.82	White	A	67%	\$\$
	(FL) 	2' x4' x3/4"	Class A	460	.70 	38 	.82	White	B, C, D	67%	\$\$
Frost Pedestals I Panels Triple-step scoring	(PE/IL) 	2' x2' x3/4"	Class A	400	.70 	35	.82	White	E	67%	\$\$\$

<b>Pedestals I</b>	<b>RENDITIONS™<sup>3</sup></b>
	

<b>Patterns</b>	<b>A</b> DONN® DX®/ DXL™	<b>B</b> CENTRICITEE™	<b>C</b> FINELINE® 1/8	<b>D</b> FINELINE	<b>E</b> CENTRICITEE
<b>Grid Profile Options</b>					

**ASTM E1264 classification**  
 Type III, Form 4, Pattern E  
**ASTM E84 surface burning characteristics**  
 Class A  
 Flame spread: 25  
 Smoke developed: 15  
**Weight**  
 1.55 lb./ft.<sup>2</sup>  
 1.60 lb./ft.<sup>2</sup> (Pedestals)

**Thermal resistance**  
 R-1.6 (Class A)  
 R-1.1 (FIRECODE™)  
**Maximum backloading**  
 See Warranty for details.  
**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.  
**Impact resistance**  
 ASTM C369 – tested to min. 190 lbf. for 1/4" depression by a 2" steel ball.

**Texture**  
 The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production date code.

**Footnotes**  
 1. LR values are shown as averages.  
 2. For details, see the Recycled Content selector.  
 3. See RENDITIONS Face-Routed Ceiling Panels (IC327) in USG Specialty Ceilings binder for more information.

**SAFETY FIRST!**  
 Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.