

# Sheetrock® MH Speed-TEX™ Ready-Mixed Spray Texture



## For a variety of light, appealing textures in interiors.

- For use over gypsum panels
- Superior open time for hand-tooled knockdown finishes
- Excellent surface relief (standout)
- Low-shrinkage formula

### Description

SHEETROCK® brand MH SPEED-TEX™ ready-mixed spray texture is a ready-mixed formulation for interior, above-grade surfaces. Use it to create light texture patterns known as crow's foot or stipple. Also suitable for orange peel and spatter knockdown.

SHEETROCK MH SPEED-TEX texture is an economical, unaggregated product ready for spray at the desired texturing consistency. It produces a light texture on drywall surfaces. Excellent coverage qualities help conceal minor surface defects. Product dries to a soft-tone white finish.

### Features and Benefits

SHEETROCK MH SPEED-TEX texture creates light texture patterns for a modern look. Designed to be applied over interior gypsum drywall ceiling surfaces, this texture applies quickly and easily and dries to a hard white finish ready for next-day decorating or painting. The texture designs these products achieve effectively forgive and conceal minor surface imperfections. SHEETROCK MH SPEED-TEX texture also provides lower shrinkage than texturing with joint compound, resulting in less cracking and a more durable finish.

- Creates a light, attractive texture
- Conceals minor surface defects in ceilings and walls
- Provides excellent coverage; dries fast
- Low-shrinkage formula
- Excellent surface relief (standout)

### Use Instructions

- This product is supplied at application viscosity. Do not dilute the texture.
- Do not add any material to this product.
- Keep equipment clean to prevent contamination of the product.

### Preparation

Surfaces must be dry, clean and sound. New drywall installation should be finished to a level adequate to prevent any joint flashing or irregularities from showing through the texture finish. Reinforce and conceal drywall joints using SHEETROCK® brand MH TUF-TAPE™ joint tape and SHEETROCK® brand MH TUF-SET™ HES setting compound. Fill all fastener depressions with joint compound. Smooth surface scratches and scuffs. Correct plane irregularities; these are accentuated by sharp, angular lighting. When prepared surfaces are dry and free of dust, apply a prime coat of SHEETROCK® brand First Coat™ primer or a quality, interior flat latex wall paint having high solids content. Primer should be applied undiluted and allowed to dry before further decorating.

### Product Data

**Storage:** Store at room temperature in a dry location. Protect from freezing, extreme heat and exposure to direct sunlight. Keep tightly sealed. Lids and caps must be secured when transporting totes.

**Color:** White. Not washable unpainted

**Tinting:** Not recommended. Overpaint when dry

**Shelf Life:** Up to six months under protected storage conditions

**Packaging:** 275-gallon tote, 4.5-gallon pail

**Submittal Approvals:**

<b>Job Name</b>	
<b>Contractor</b>	<b>Date</b>

**Warning**

Spray mist or dust generated from application or sanding may cause eye, skin, nose, throat or respiratory irritation. Avoid inhalation of mist/dust and eye contact. Use proper ventilation to reduce mist/dust exposure. If misty/dusty, wear a NIOSH/MSHA-approved respirator. Prolonged and repeated exposure to respirable talc may cause lung disease. Wear appropriate eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists,

call physician. Do not ingest. If ingested, call physician. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Close container and discard properly. Product safety information: (800) 507-8899 or [www.usg.com](http://www.usg.com)

**KEEP OUT OF REACH OF CHILDREN.**

**Trademarks**

The following trademarks used herein are owned by United States Gypsum Company: First Coat, SHEETROCK, SPEED-TEX, TUF-TAPE, TUF-SET.

**Notice**

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

**Safety First!**

Follow good safety and industrial hygiene practices during handling and installation of products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.

