

Minimize downtime and apply
floor coverings within 15 hours



Levelrock® Quik-Top™

Floor Underlayment

- Premium poured flooring product with self-drying technology
- Can be used with any finished floor application
- No shot blasting required
- Eliminates the need for sealing prior to floor-covering installation
- Can be used with stains and sealers to provide a finished floor



Now, thanks to an innovative USG technology,¹ downtime due to floor rehab and repair work can be minimized. A floor typically can be prepped, poured and floor coverings applied within one day, allowing businesses to reopen the next day.

**Product
Performance**

Industry-Changing Technology

It is now possible to repair floors in one day with LEVELROCK® QUIK-TOP™ floor underlayment. This innovative product is ideal for any job that requires a fast turnaround, such as renovations of retail space, restaurants, casinos, office space, hospitals and airports.

High Performance

LEVELROCK QUIK-TOP floor underlayment exceeds commercial vinyl floor-covering requirements as a high-performance underlayment whose exceptional surface hardness resists indentation due to high compressive strengths of 5000–6000 psi.*

Easy Preparation

LEVELROCK QUIK-TOP floor underlayment does not require shot blasting. Concrete simply needs to be clean, sound, dry and primed.

Finishing Flexibility

Designed specifically for commercial and institutional rehab projects, LEVELROCK QUIK-TOP floor underlayment is suitable for a variety of floor coverings. It also can be used by itself as a finished floor with an appropriate coating system, and can be stained prior to application of a clear coat wear surface.²

LEVELROCK QUIK-TOP floor underlayment also speeds finished floor-covering applications. Once the floor underlayment is dry, floor-covering adhesive may be applied without sealing the underlayment.

Note *Compressive strengths published herein were achieved under controlled laboratory conditions. Actual field results may differ due to environmental conditions; inconsistent proportioning of field applied water and LEVELROCK floor underlayment, as well as differences in mixing/pumping equipment.

Footnote

1. Patent pending.
2. USG does not warrant the performance of the wear surface coating. Consult coating manufacturer for suitability of use, field bond test and coating warranty.

Product Information

See levelrock.com for the most up-to-date product information.

Trademarks

The following trademarks used herein are owned by United States Gypsum Company or a related company: LEVELROCK, QUIK-TOP, USG, USG in stylized letters.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss

caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

Safety First!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

