

True Wood



True Wood, Maple Linear

LEED Credits
Recycled Content: 97%

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●		●

Features and Benefits

- The elegance, warmth and majesty of true wood
- Natural wood veneers
- Standard module sizes of 2' X 2', 2' X 4' and linear panels
- Perforated options, with an integrated acoustical backer
- FSC certified
- Class A fire rating per ASTM E1264

Applications







- Schools
- Healthcare
- Conference rooms
- Restaurants
- Retail stores




2' x 2' True Wood Panels

Call 888.874.2450 for samples



	Edge	Panel Size	Class	Grid Options	Smooth (Unperforated)		Perforated (W100)**		Perforated (W200)**		Perforated (W300)**		Perforated (W400)**	
					NRC	CAC	NRC	CAC	NRC	CAC	NRC	CAC	NRC	CAC
														
True Wood Lay-in Panels	FL	2'x2'x3/4"	Class A	E, F, G	—	37	.60	—	.30	—	.70	—	.40	—
		2'x4'x3/4"	Class A	E, F, G	—	37	.60	—	.30	—	.70	—	.40	—
	SL	2'x2'x3/4"	Class A	D	—	37	.60	—	.30	—	.70	—	.40	—
		2'x4'x3/4"	Class A	D	—	37	.60	—	.30	—	.70	—	.40	—
True Wood Accessible Reveal Panels	AR	2'x2'x3/4"	Class A	D	—	37	.60	—	.30	—	.70	—	.40	—
		2'x4'x3/4"	Class A	D	—	37	.60	—	.30	—	.70	—	.40	—

** All USG True Wood perforated panels include an integrated acoustical backer to provide a high level of sound performance without the expense and additional labor of infill panels.

Panel Size	Class	Grid Options	NRC	CAC	Trim Options
					
Nominal 4" Panel 3 3/4" x 8'	Class A	DWSS	.40	—	6" Nominal (3 3/4" x 8')
Nominal 6" Panel 5 1/4" x 8'	Class A	DWSS	.40	—	

Linear panels have a black fabric backing that overlaps panel to panel to create a clean black look in the reveal.

	D DX/DXL	E CENTRICITEE DXT	F FINELINE® DXF	G FINELINE® 1/8 DXFF
Grid Profile Options				

Perforation Options*	Pattern Number	Hole (mm)	Spacing (mm)	% Open Area
	W100	6	16	10
	W200	6	32	3
	W300	8	16	20
	W400	8	32	5

* For 2'x2' and 2'x4' panels only

**Physical Data/
Footnotes**

Product literature
 Data sheet: IC558
 Finishes Sheet: IC559
 Tech Guide: IC561
ASTM E84 surface burning characteristics
 Class A
 Flame spread: 20
 Smoke developed: 15
ASTM E1264 Classification
 Composite — Class A Fire Performance

Weight
 3 lb./sq. ft.
Material
 No added urea formaldehyde core, with face cut veneers

Footnotes
 Color disclaimer: Printed and/or online color swatches are only reproductions of actual standards and will vary in appearance due to differences in monitor and printer output. These representations should not be used to finalize color selection(s).

Wood Disclaimer: Wood is a natural grain product with variations in grain, texture and color often ranging from light to dark, thereby affecting the surface look. Product finishes are spray applied stain or sealer coats

