



MILLENNIA Panels with *CLIMAPLUS* Superior Performance/
DONN DX/DXL Suspension System

LEED Credits

Recycled Content: 75%
CLIMAPLUS Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- Market’s fastest-installing fine-textured ceiling is an economical alternative to face-laminated panels.
- NRC meets general office acoustical needs for sound absorption.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/ 95% relative humidity without visible sag when used with a DONN® brand suspension system.

Applications

- Retail stores
- Hospitality
- Office and conference areas
- Transportation terminals

Substrate

- X-Technology mineral fiber


















Fine-textured panel

Call 888.874.2450 for samples



White

30
 Year System Warranty
 – No visible sag
 – Mold/mildew protection

	Edge	Panel Size	Class	Item No.	UL Classified			Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ⁵	Panel Cost
					NRC	CAC Min. ³	LR ⁴						
MILLENNIA CLIMAPLUS Panels	SQ 	2'x2'x3/4"	Class A	76505	.70	35	.85	White	A, B, C	Low		75%	\$\$
		2'x4'x3/4"	Class A	78505	.70	35	.85	White	A, B	Low		75%	\$\$
	SLT 	2'x2'x3/4"	Class A	76705	.70	35	.85	White	D	Low		75%	\$\$
		2'x4'x3/4"	Class A	78705	.70	35	.85	White	D	Low		75%	\$\$
	FLB 	2'x2'x3/4"	Class A	76907	.70	35	.85	White	E, F, G	Low		75%	\$\$
		2'x4'x3/4"	Class A	76901	.70	35	.85	White	E, F, G	Low		75%	\$\$
MILLENNIA CLIMAPLUS Tile^{6,7}	BESK 	12"x12"x3/4"	Class A	70003	.60	40	.85	White	H	Low		75%	\$\$\$\$
MILLENNIA CLIMAPLUS Illusion Two/24 Panels The look of 2'x2' panels	SLT ⁹ 	2'x4'x3/4"	Class A	78780	.70	35	.85	White	D	Low		75%	\$\$
	ILT ⁹ 	2'x4'x3/4"	Class A	78080	.70	35	.85	White	I	Low		75%	\$\$

Illusion Two/24

Patterns












Legend

 **Low Emissions (VOC Class)**

Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

 **CLIMAPLUS Superior Performance¹⁰**

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold/mildew, fungi, yeast, algae, and Gram-positive and Gram-negative odor/stain-causing bacteria.

A	B	C	D	E	F	G	H	I
DX®/DXL™	DXW™	CENTRICITEE™ DXT	DX/DXL	CENTRICITEE DXT	FINELINE® DXF	FINELINE® 1/8 DXFF	DX®/DXL™ Concealed	CENTRICITEE DXT
								

Grid Profile Options

Physical Data/ Footnotes

Product literature
Data sheet: SC1824

ASTM E1264 classification
Type III, Form 1, Pattern E, G

ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 50

Weight
1.02-1.05 lb./sq. ft. (panels and tile)

Thermal resistance
R-2.0

Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Patented technology
This product's unique combination of sag resistance and sound performance results from a technology covered by U.S. Patent No. 5,250,153.

Footnotes

- Applies when USG acoustical ceilings recycling program is utilized.
- Dependent on location; see Sustainability selector.
- Adding sound masking can be as effective as using a ceiling panel with a higher CAC rating, providing increased privacy between enclosed office spaces.
- LR values are shown as averages.
- For details, see Sustainability selector.
- Contact USG for adhesive recommendations for 12"x12" glue-up applications.

- Not UL Classified for acoustics.
- Panels have a 15/16" routing.
- Panels have a 9/16" routing.
- Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold/mildew, fungi, yeast, and odor/stain-causing Gram-positive and Gram-negative bacteria. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPLUS Ceilings Certification of Performance* (SC2451).