



Orion™ 210 *ClimaPlus™*



Fine-textured panel



Features and Benefits

- Washable vinyl face for easy maintenance.
- Very good sound absorption (NRC .65) at mid-range price.
- Lightweight for quick installation.
- *CLIMAPLUS™* 15-year system warranty to withstand conditions up to 90 °F (32 °C)/90% relative humidity without visible sag when used with a USG *Donn®* brand suspension system.

Applications

- Schools
- Convenience stores
- Corridors
- Discount stores
- Grocery stores
- Healthcare
- Retail stores

Substrate

X-Technology mineral fiber




























Orion 210 ClimaPlus

Acoustical Ceilings

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC1834



UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Panel Cost
ORION 210 CLIMAPlus Panels	(SQ) 	Class A	62111	.65	25	.76	White	A, B, C, D, E	81%	\$
		Class A	64111	.65	25	.76	White	A, B, D, E	81%	\$
Grid Profile Options	A DONN® DX®/ DXL™ 	B DONN® DXW™ 	C CENTRICITEE™ 	D ZXLA™ 	E AX™ 					
										
										
										
										

ASTM E1264 classification
Type IV, Form 1 and 2, Pattern CE
ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 25
Weight
0.58 lb./sq. ft.

Thermal resistance
R-1.6
Maximum backloading
See Warranty for details.
Maintenance
Can be cleaned easily with a damp sponge.

Patented technology
This product's unique combination of vinyl facings, sag resistance, and sound performance results from a technology covered by U.S. Patent No. 5,250,153.

Footnote
1. LR values are shown as averages.
2. For details, see the Sustainability selector.

Safety First!
Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company: AX, CENTRICITEE, CLIMAPlus, DONN, DX, DXL, DXLA, DXW, ORION, USG, ZXLA.

SC1834/rev. 6-06
© 2006, USG Interiors, Inc.
Printed in U.S.A.