

Celebration Panel with D250 Perforation and Acoustical Backer, Installed Over Existing $2^{\prime}x\,4^{\prime}$ 15/16" Suspension System and Acoustical Ceiling Panels

Celebration[™] Renovation Clip





Features and Benefits

- Refinishes an outdated suspended ceiling with sleek Celebration™ Metal Ceiling Panels or True™ Acoustical Ceiling Panels.
- Accents high-profile areas without additional, specialty suspension systems.
- Allows enhanced acoustical performance.
- Fits standard 15/16" metal suspension systems by any manufacturer.
- Significantly reduces renovation costs and debris.
- Clips made of flame-resistant, selfextinguishing resin to achieve highest UL flame rating for plastic.

Applications

- Anywhere 15/16" face T- Bar is used
- Lobbies
- Accent areas
- Contemporary office environments
- Retail spaces
- Health care
- Educational

Celebration Clip

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number IC479

Product Information	Materials	Clip made	de of injection-molded flame-resistant, self-extinguishing resin.						
illorillation	Module Size	Module Size Adapts 2' x 2' and large-format Celebration-edge (with Square Edge and Shadowline edge details with				(CEL) ceiling panels to existing 15/16"-face suspension systems. Can be used on installations thout removing the existing ceiling panels.			
	Suspension System	Suspension An existing standard 2' x 2' or 2' x 4' roll-formed, existing suspension system is square and structura			, all-steel or aluminum 15/16"-face suspension system by any manufacturer. Ensure that the rally sound and that the plenum is free of maintenance problems (e.g. roof leaks, mold, or mildew).				
Perspective							Perimet	existing wall existing molding existing ceiling panel C8 clip field-cut panel us8 channel molding	
Design Concept	ts	CELEBRATIO	N Renovation patterns for 2' x 2'	. 2' x 4'	, and 2' x 6' suspensio	n modules.			
2' x 2'	Square			,	2'x 2' and 2'x 4'	·			
2′ x 4′	Running Bond		Herringbone		2' x 2' and 2' x 6'	Weave			
	Paver		Stack		2′ x 6′	Stack	Stack		
	Supporting techn literature IC478, Installation I IC308, CELEBRATION I Panels Data Sheet SC2443, TRUE Acou Panels Brochure	nstructions Metal Ceiling	Code approval The Donn Celebration Renovation Clip is made of flameresistant, self-extinguishing material and meets V-0 classification as defined by UL 94. Footnote 1. Spot-check squareness by measuring the opposite diagonals of grid modules; diagonal lengths must be wit 1/8". (If using 3'-4'-5' triangmethod, triangle must close within 1/8".)		SAFETY FIRST! Follow good safety and hygiene practices durin and installation of all p and systems. Take nec precautions and wear priate personal protect ment as needed. Read	g handling roducts essary the appro- ive equip-	safety data sheets and related literature on products before specification and/or installation. Patents Patents pending.		

Manufactured by USG Interiors, Inc.

125 South Franklin Street Chicago, IL 60606

