

Millennia[®] ClimaPlus[™] High NRC



Smooth textured panel

Features and Benefits

- Market's fastest-installing smooth ceiling is an economical alternative to face-laminated panels.
- NRC of .75 meets the demanding sound control needs of open-plan offices.
- CLIMAPLUS[™] 30-year Lifetime System
 Warranty to withstand conditions
 up to 104 °F (40 °C)/95% relative
 humidity without visible sag when
 used with USG's Donn® Brand
 Suspension Systems.

Applications High NRC

- Libraries
- Open-plan offices
- · Reception and lobby areas

MILLENNIA® High NRC Panels with CLIMAPLUS™ Performance/Donn® Brand FINELINE® Suspension System

$\begin{aligned} & \text{Millennia}^* \textit{ClimaPlus}^{\text{\tiny{TACoustical Ceilings}}} \\ & \text{High NRC} \end{aligned}$

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC1851

| CLIMAPLUS" | | | | | | (U) UL | Classified | | | | | |
|---------------------------------------------|-------------------------|--------------------------------------------|-------------------|-------------|---------------|-------------------|-------------|-----|-------|-----------------|----------------------------------|------|
| Non-Sag Warranty | Edge | Pan | el Size | Class | Item No. | NRC | CAC Min. | LR1 | Color | Grid Options | Recycled Content ² | |
| MILLENNIA® CLIMAPLUS™ High NRC Panels | (SLT) | 2'x2'x3/4" | | Class A | 76201 | .75 | 30 | .85 | White | А | 72% | \$\$ |
| | (FLB) | (FLB) 2 ′ x2 ′ x3/4 ″ | | Class A | 76302 | .75 (1) | 30 | .85 | White | B, C, D | 72% | \$\$ |
| | A Donn® DX®/ DXL™ | | B Centricitee™ | C FINELINE® | 1/8 D FINE | LINE | | | | | | |
| Grid Profile Options | | | | | | |] | | | | | |

ASTM E1264 classification Type III, Form 1 or 2, Pattern G ASTM E84 surface burning characteristics

Class A Flame spread: 25 Smoke developed: 25 Weight 1.04 lb./ft.² Thermal resistance R-2.6

Maximum backloading See Warranty for details. Maintenance

Can be cleaned easily with a soft brush or vacuum. **Patented technology**This product's unique combination of sag resistance and sound performance results from a technology covered by U.S. Patent No. 5,250,153.

Footnotes

LR values are shown
 as averages.
 For details, see the Recycled
 Content selector.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

