

- ARDEX Substrate Preparation Products
- ARDEX Tile & Stone Products
- HENRY Adhesives



#### The Most Comprehensive Flooring Installation Solution




ARDEX Engineered Cements and The W.W. Henry Company, industry leading manufacturers of high performance flooring installation products, have combined to offer the SystemOne™ Total Solution, the most complete flooring installation solution available in the industry. Architects, specifiers and contractors have ranked flooring installations as one of the most challenging aspects of any building project. SystemOne Installation Solutions provide the ultimate peace of mind through the use of trusted and fieldproven ARDEX high-performance substrate preparation products, HENRY® premium flooring adhesives and ARDEX high-quality tile & stone installation products.

When utilizing a complete system of ARDEX and HENRY high-performance installation products, combined with ARDEX Proper Prep™ installation guidelines, you can rest assured that your flooring installations will be right the first time…every time!

#### **Industry Best Warranty**

We're so confident, we back SystemOne Installations with the industry's best and most comprehensive "full replacement" warranties. From the flooring, to the installation products and even the labor, we leave nothing to chance. A SystemOne Warranty minimizes your risk and provides you the ultimate peace of mind.



#### **Unmatched Support**



SystemOne installations not only include best in class products and industry best warranties, they also have the complete support of the ARDEX / HENRY Architectural Team, more than 80 Field Sales Professionals and our highly-experienced Technical Services Team. The ARDEX / HENRY support teams provide a guaranteed 24 hour response, as well as on-site support throughout the entire installation process (before, during and after project completion).

ARDEX also provides specialized training for flooring installation contractors that certifies them as a SystemOne™ Installation Professional. The result is a network of highly skilled flooring installation professionals located throughout North America.

The SystemOne Solution...ultimate peace of mind & your best choice for installation success!

### **ARDEX/HENRY® Products**

				10 2000	
System One	Moisture Remediation	Self-Leveling	Patching	Adhesives	
CARPET					
10 year/ Ltd. Full Replacement	MC	K 15 <sup>®</sup> , LU 100 <sup>™,</sup> GS-4 <sup>™</sup>	FEATHER FINISH®, SD-P®, FORTI FINISH™	HENRY®, 391, 351, 451, 248	
5 year/Ltd. Full Replacement		V 1200™			
VINYL-BACKED CARPET TILE					
10 year/ Ltd. Full Replacement	MC	K 15®, LU 100, GS-4	FEATHER FINISH®, SD-P®, FORTI FINISH™	HENRY® 630	
5 year/Ltd. Full Replacement		V 1200			
SOLID VINYL PLANK, TILE & SHEET					
10 year/ Ltd. Full Replacement	MC	K 15 <sup>®</sup> , LU 100, GS-4	FEATHER FINISH®, SD-P® FORTI FINISH™	HENRY® 422, 640	
5 year/Ltd. Full Replacement		V 1200			
VINYL COMPOSITION TILE (VCT)					
10 year/ Ltd. Full Replacement	MC	K 15®, LU 100, GS-4	FEATHER FINISH®, SD-P®, FORTI FINISH™	HENRY® 430 GL	
5 year/Ltd. Full Replacement		V 1200			
WOOD					
10 year/ Ltd. Full Replacement	MC	K 15 <sup>®</sup> , LU 100, GS-4	FEATHER FINISH®, SD-P®, FORTI FINISH™	HENRY® 1171N, 971	
5 year/Ltd. Full Replacement		V 1200			



# ARDEX Self-Leveling Underlayments and Patching Products

<b>ARDEX</b>	ARDEX K 15®	ARDEX V 1200™	ARDEX GS-4™	ARDEX LU 100™	ARDEX FEATHER FINISH <sup>®</sup>	ARDEX FORTI FINISH™	ARDEX SD-P®
Formulation Type	Portland Cement	Portland Cement	High strength Gypsum & Portland cement	High strength Gypsum & Portland cement	Portland Cement	Portland Cement	Portland Cement YES NO NO YES
Over concrete	YES	YES	NO	YES**	YES YES YES YES YES	YES NO YES YES NO	
Over wood floors	YES	NO	YES	NO			
Over non-water-soluble adhesive residue on concrete	YES	YES	NO	YES**			
Over ceramic tile and terrazzo	YES	YES	NO	YES			
Over distressed gypsum	NO	NO	YES**	NO			
Over existing patching and leveling materials	naterials INO		NO	YES	NO	NO 1/2"*	NO 1"
Max. installation thickness without aggregate			2"	2"	1/2"*		
Max. installation thickness with aggregate	5"	N/A	5"	5"	N/A	N/A	3"
Curing time before installation of flooring	16 hours	1 to 3 days	2 to 3 days (mat test)	2 to 3 days (mat test)	When hard (approx. 15 to 30 min.)	When hard (approx. 15 to 30 min.)	When hard (approx. 1 hour)
Compressive strength PSI (ASTM C109/ mod air cure only)	4100	4000	4000	4100	4200	7800	4200
Water-resistant	YES	YES	NO	NO	YES	YES	YES
Pumpable	YES	YES	YES	YES	NO	NO	NO
Trowelable	NO	NO	NO	NO	YES	YES	YES

<sup>\*</sup>For additional information refer to the product technical brochure

## **ARDEX Tile & Stone Products**

1	tile & stone Installation System	Substrate Prep -Self-Leveling -Patching	Setting Materials	Waterproofing	Grouts	
	TILE & STONE INSTALLATION					
	10 year/ Ltd. Full Replacement	EB 2, Liquid Backerboard™, TL 1000™, TL Patch™ (Other ARDEX Substrate Prep Products)	X 9™, FB 9 L™ X 7 Plus™, X 5™ S 16™, S 14™ WA™	8+9™	Flex Sanded™ Flex Unsanded™ WA	
3	5 year/Ltd. Full Replacement	TL 700™	D 14™, X 4™ X 3™	S 1-K™		



## **HENRY®** Adhesives

HENRY	Multi- Purpose	Multi- Purpose Pressure Sensitive	Carpet		Seam Sealer	Vinyl Plank Tile Sheet		Vinyl Composition Tile (VCT)	Linoleum Sheet	Wood Flooring		
14	356C	630	351	391	451	248	422	640 GL	430 GL	582	1171N	971
CARPET												
Jute			X	Х	Х	Х						
ActionBac®			Χ	Х	Х	Х						
Urethane Foam			X	X	X	Х						
Non-backed Needle Punched			х	х	х	х						
Latex Foam			X	Х	Х	Х						
Unitary			Х	Х	Х	Х						
Unitary ActionBac®			X	X	X	X						
Hot Melt			X	X	X	X						
Woven	6		X	X	X	Х						
Urethane Laminate			X	Χ	Χ	X						
Vinyl Back Carpet Tile		х										
RESILIENT TILE												
VCT									Х			
Solid Vinyl Tile & Plank							Х	Х				
RESILIENT SHEET												
Residential & Commercial Felt-Back	X											
Vinyl Backed							Х	Х				
Linoleum Sheet										Х		
WOOD												
Parquet											Х	Х
Engineered Wood											Х	Х
Solid Wood											Х	Χ

