

ARDEX GS-4 Self-Leveling, Repair Underlayment for Gypsum & Wood Subfloors

A self-leveling underlayment used to smooth and repair an existing gypsum substrate that is otherwise unsuitable to receive new finish flooring.



Product Capabilities:

ARDEX GS-4 is intended for use as a remedial material for distressed gypsum subfloors that have suffered degradation. It can also be used to smooth over building code-approved structurally sound wood, and over gypsum or wood subfloors that contain hydronic heating tubes or low voltage electrical in-floor heating systems. It can be installed from 1/4" up to virtually any thickness to achieve the desired flatness tolerance. It can be walked on after 3 hours, and floor covering can be installed as soon as the underlayment has dried sufficiently for the floor covering selected. The drying time is a function of temperature, humidity, and the thickness at which the material is applied.

Benefits:

- A blend of high strength gypsum and Portland cements
- Repairs existing gypsum and wood substrates above grade prior to the installation of new floor covering
- Hardens and dries faster than other gypsum products
- Needs no special curing
- Easy to mix and apply
- Install from 1/4" up to virtually any thickness, can be tapered to 1/16"
- Recommended for use over structurally sound plywood, OSB, and strip wood flooring
- Install floor covering in 2-3 days
- Suitable for use with indoor hydronic and electric radiant heating systems
- Use for interior floors only

Click Below for Technical and Specification Documents:

[Tech Info & Installation \(English\)](#)