

ARDEX K 301™ Exterior Self-Leveling Concrete Topping & Underlayment

ARDEX K 301™ is an exterior self-leveling Portland cement-based topping and underlayment for fast-track resurfacing and smoothing. Makes spalled or damaged concrete look like new.



Product Capabilities

Can be used for exterior and interior applications over concrete, porous tile and certain non-porous surfaces when properly prepared – on, above or below grade. ARDEX K 301 can be sealed to create a concrete wear surface for commercial, light industrial and residential applications including;

- Sidewalks
- Driveways
- Loading Docks
- Parking Garages
- Patios / Porches
- Decks / Balconies
- Plazas
- Plus many more applications

It can also be used as an underlayment for finish flooring, as well as on permanently wet areas and under moisture remediation systems such as the ARDEX MC™ Moisture Control System.

Installs from 1/4" to 3/4" in one application, and up to 2" with the addition of appropriate aggregate. Pourable or pumpable when mixed with water. Seeks its own level and produces a smooth, flat, hard surface. Hardens quickly and dries fast without shrinking, cracking or spalling.

Benefits:

- Portland cement based
- Walk on in 2 to 3 hours
- Freeze – thaw resistant
- Installs at 1/4" – 3/4" neat up to 2" with aggregate
- Completely water resistant
- Exterior or interior applications
- On, above or below grade
- For use under ARDEX MC Moisture Control

Click Below for Technical and Specification Documents:

[Tech Info & Installation \(English\)](#)