

RS22

.22 Caliber Single Shot Tool Trigger Operated Powder Actuated Tool



ADVANTAGES

- | Designed for frequent use providing professional fastening results in a variety of concrete, masonry or steel applications.
- | The RS22 is a traditional trigger operated tool.
- | Positive barrel and load retention prevents barrel from opening freely, allowing easy horizontal and overhead fastening.
- | Powder load automatically ejects after each use.
- | Ergonomic design for operator comfort.
- | Heavy-duty all-steel construction.
- | 90 day warranty.

SPECIFICATIONS

- | Uses standard .22 caliber single shot powder loads 2 (Brown), 3 (Green), 4 (Yellow)
- | Weight: 4.1 pounds
- | Length: 14-3/4 inches
- | Muzzle Bushing O.D.: 3/4"
- | Maximum Pin Length: 2-1/2" (3" w/washer)

MOST COMMON FASTENERS

THREAD STUD #	SHANK LENGTH		MOST COMMON APPLICATION
	IN	MM	
1524SDP (washed)	3	76.2	2" x 4" to concrete
1516SDC (washed)	2 -1/2	63.5	2" x 4" to concrete
1506	3/4	19.1	Drywall track to concrete



2" x 4" to concrete slab



Track to floor

.22 Caliber Single Shot Tool

FOR SPECIFIC PIN AND LOAD INFORMATION SEE PAGES 24-38