

health design™

Who says a sterile environment needs to look sterile? Enter FLEXCO® Health Design™ Solid Vinyl Tile, the antifungal, antibacterial flooring that can handle the toughest scrutiny of clean rooms, yet offer a style that's catching on everywhere. Substance. Style. Health Design™ Solid Vinyl Tile adds more design options while providing the cure for chips, abrasions, cracking and indentations. May contribute to LEED® CI and NC credits MR 5 and MR 6.

features and benefits

- > Easily buffed to a shine. No waxing is required, so maintenance costs are less.
- > Built-in antimicrobial barrier helps control bacteria and fungi.
- > .080" gauge solid vinyl is available in three sizes: 12" x 12", 24" x 24" and 36" x 36".
- > 12" x 12" tiles are Precision Squared™ to ensure an ultra-precise fit.
- > Flexible for quick and easy flash coving.
- > Dense composition meets ASTM F 1700 and makes floor maintenance easier.
- > May be seamlessly installed with FLEXCO®'s Vinyl Welding Beads for clean rooms and areas that have strict requirements for added hygiene.
- > 16/86 Multiperformance Tile & Tread Adhesive contains an antimicrobial agent for added protection against mold and bacteria.
- > Exceeds ADA recommendations for slip resistance on flat surfaces.



the end user

health design™

"Health Design™ tile was the right solution for our client. The demand was for a sturdy, attractive and easy to maintain flooring product. The laboratory is busy all the time, Health Design™ tile performs great."

– Koeckritz International Rolling Meadows IL.





specifications

order prefix:

HD = Health Design™ Vinyl Tile

Health Design™ Vinyl Tile	12" x 12"	24" x 24"	36" x 36"
Gauge	.080"	.080"	.080"
Pieces/Ctn (lb)	70	20	10
Sq Ft/Ctn	70	80	90
Weight	70	80	90

Note: Add HW to color number for pre-grooved Heat Weld tiles (e.g., HD-035HW) available in 24" x 24" and 36" x 36" tile sizes.

Must be installed using FLEXCO® 16/86 Multipurpose Tile and Tread Adhesive or 77 Solvent-Free Epoxy Adhesive.

contract[®]

Scuffs out. Style in. With FLEXCO[®] solid vinyl tile, the homogenous color extends through the entire tile thickness. So, instead of the minor scuffs that leave a major mark on vinyl composition tile (VCT), FLEXCO[®] solid vinyl tile stays looking cleaner for a longer period of time. FLEXCO[®] vinyl compounds are a brilliant white, which means our colors look brighter for a longer period of time and provide a cleaner look than the grayish white of some VCT products. May contribute to LEED[®] CI and NC credits MR 5 and MR 6.

features and benefits

- > Easily buffed to a shine. No waxing is required, so maintenance costs are less.
- > Built-in antimicrobial barrier helps control bacteria and fungi.
- > 1/8" gauge solid vinyl is available in three sizes: 12" x 12", 24" x 24" and 36" x 36".
- > 12" x 12" tiles are Precision Squared™ to ensure an ultra-precise fit.
- > Flexible for quick and easy flash coving.
- > Dense composition meets ASTM F 1700 and makes floor maintenance easier.
- > May be seamlessly installed with FLEXCO[®]'s Vinyl Welding Beads for clean rooms and areas that have strict requirements for added hygiene.
- > 16/86 Multiperformance Tile & Tread Adhesive contains an antimicrobial agent for added protection against mold and bacteria.
- > Exceeds ADA recommendations for slip resistance on flat surfaces.



the end user

contract[®] solid vinyl tile

Somerset Medical – Somerville, NJ
Donna Thompson, IIDA Project Manager,
Interior Design
Specified by ARRAY in King of Prussia, PA

Array chose FLEXCO[®] Flooring for this hospital addition of a 35-bed Medical/Surgical Unit and 35-bed Oncology Unit for a number of reasons. One of the challenges healthcare designers face is trying to break up the long, straight 8'-0" width hospital corridor with a flooring product appropriate for the use. The FLEXCO[®] tile provided a 36" square solid vinyl tile format that allowed a creative departure from other 12" square materials. It enabled an opportunity to focally delineate the nurse stations and other public destinations. Secondly, it was an attractive product with the antimicrobial, antifungal properties. From the facility point-of-view, the no-wax aspect was compelling.





specifications

order prefix:

C = Contract® Vinyl Tile

Contract® Vinyl Tile	12" x 12"	24" x 24"	36" x 36"
Gauge	1/8"	1/8"	1/8"
Pieces/Ctn (lb)	45	14	6
Sq Ft/Ctn	45	56	54
Weight	54	67	65

Note: Add HW to color number for pre-grooved Heat Weld tiles (e.g., C-6HW) available in 24" x 24" and 36" x 36" sizes. Must be installed using FLEXCO® 16/86 Multiperformance Tile & Tread Adhesive or 77 Solvent-Free Epoxy Adhesive.

appeal™

It's easy to like Appeal™ solid vinyl floors from FLEXCO®. After all, with its interesting design, long-lasting color and durable construction, this line offers you the perfect combination of fashion, flexibility and functionality.

In addition, Appeal™ tile significantly outperforms vinyl composition tile. Because Appeal™ tile combines durable, solid vinyl construction and simple maintenance requirements, it guarantees a much better return on investment – in the short term and over the long run. May contribute to LEED CI and NC credits MR 5 and MR 6.

features and benefits

- > Easily buffed to a shine. No waxing is required, so maintenance costs are less.
- > Built-in antimicrobial barrier helps control bacteria and fungi.
- > 1/8" gauge solid vinyl is available in three sizes: 12" x 12", 24" x 24" and 36" x 36".
- > 12" x 12" tiles are Precision Squared™ to ensure an ultra-precise fit.
- > Tough, nonporous, homogeneous construction features color that goes all the way through the tile.
- > Flexible for quick and easy flash coving.
- > Dense composition meets ASTM F 1700 and makes floor maintenance easier.
- > May be seamlessly installed with FLEXCO®'s Vinyl Welding Beads for clean rooms and areas that have strict requirements for added hygiene.
- > 16/86 Multipurpose Tile & Tread Adhesive contains an antimicrobial agent for added protection against mold and bacteria.
- > Exceeds ADA recommendations for slip resistance on flat surfaces.





specifications

order prefix:

A = Appeal™ Vinyl Tile

Appeal™ Vinyl Tile	12" x 12"	24" x 24"	36" x 36"
Gauge	1/8"	1/8"	1/8"
Pieces/Ctn (lb)	45	14	6
Sq Ft/Ctn	45	56	54
Weight	54	67	65

Note: Add HW to color number for pre-grooved Heat Weld tiles (e.g., C-6HW) available in 24" x 24" and 36" x 36" sizes.

Must be installed using FLEXCO® 16/86 Multiperformance Tile & Tread Adhesive or 77 Solvent-Free Epoxy Adhesive.