



RECESSED ROW LAY-IN FIXTURE

IPIR-SERIES (4FT. OR 8 FT.)



APPLICATION: Ideally used where linear illumination in row formation is needed, such as: supermarkets, and department stores.

CONSTRUCTION: Made from heavy-duty iron phosphate treated CRS (Cold Rolled Steel) and finished with a high-reflectivity electromagnetic-applied powder coat for a minimum reflectance of 90%, thereby, yielding high lumen efficiency. Die formed for extra strength and rigidity.

ELECTRICAL WIRING: Supplied with a high frequency class "A" sound rating class "P" thermally protected, High Power Factor electronic ballast with total harmonic distortion of less than 10%. This multi-volt ballast will operate T8 lamps from 50/60 Hz input source of 120V through 277V. U.L. approved, CBM certified, meets CSA Standards. Complies with U.S.A. National Energy efficiency standards. Optional: Dimming

Ballast and Backup Power Pack available on special order.

ORDERING INFORMATION:

<u>LAMPS</u>	<u>LAMP TYPE</u>	<u>PART NUMBER</u>
2 EA.	32W-T8	IPIR-232/MV
2 EA.	59W-T8	IPIR-259/MV

ILLUMINATION PRODUCTS, INC.



ILLUMINATION PRODUCTS, INC.

ILLUMINATION PRODUCTS, INC.

Manufacturers of Fluorescent Lighting Fixtures