






technical data





Product	Description	Surface treatment	Total thickness	Thickness of wearlayer	Weight	Tile dimensions	Special characteristic
	Prestige decorative strip	PUR	2.5mm	0.7mm	Wood 3800g/m ² Rustic 4400g/m ²	15.2 x 91.4cm 10.1 x 91.4cm Rustic 15.2 x 91.4cm	Realistic wood and mineral effects
	Prestige decorative tile	PUR	2.5mm except Slate 2.4mm	0.7mm except Slate 2.4mm	Mineral 4400g/m ² Slate 3700g/m ²	Mineral 45.7 x 45.7cm Slate 30 x 60cm	Interlocking tiles for fast installation
	Fast track loose lay tile	PUR	5.0mm	1.0mm	7400g/m ²	635 x 635mm	Interlocking tiles for fast installation
	Fast track loose lay tile	PUR	6.0mm	2.0mm	9300g/m ²	635 x 635mm	Heavy duty interlocking tiles for fast installation
	Fast track loose lay tile	Protectsol®	5.5/5.3mm	0.85mm & 1.0mm	5400 & 5150g/m ²	50 x 50mm	Can be used with carpet tiles Ultra low maintenance

Guide to Surface Treatments: for acrylic emulsion for the whole life of the product. It is applied to our "top of the range" homogeneous products. PUR – This factory applied polyurethane treatment eases the maintenance and eliminates the need for acrylic emulsions. Subject to traffic levels emulsions may be needed over time. PUR Protect® – This factory applied polyurethane treatment multi-layered products. The treatment is guaranteed for the full life of the product and eliminates the need for costs by eliminating the need for the full life of the product. The treatment is guaranteed for the full life of the product and eliminates the need for costs by eliminating the need for the full life of the product.

Protectsol® – This factory applied patented treatment is embedded within the full thickness of the wear layer of our "top of the range" multi-layered products. The treatment is guaranteed for the full life of the product and eliminates the need for costs by eliminating the need for the full life of the product.

Sparclean® – This patented powder coated system is resistant products and has been independently proven to improve cleaning and reduce maintenance costs. The treatment provides extreme resistance soiling and staining, excellent resistance to chemicals ensuring long term durability. CAMRASO (Cleaning and Maintenance Research and Services Organisation) has shown an 86% improvement in cleaning products and a 69% improvement when compared to untreated products.

education flooring solutions

Product	Description	Surface treatment	Total thickness	Thickness of wearlayer	Weight	Sheet dimensions	Tile dimensions	Special characteristic
	Homogeneous	PUR	2.0mm	2.0mm	3450g/m ²	2 x 20m	30cm x 30cm or 60.8cm x 60.8cm	Durable – K5 classification
	Homogeneous	PUR	2.0mm	2.0mm	3450g/m ²	2 x 20m	30cm x 30cm or 60.8cm x 60.8cm	Durable – K5 classification
	Safety	Untreated	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Slip resistant: Dry: EN13893>0.3 Slip resistant: Wet: DIN 51 130 R10
	Safety	Sparclean®	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Slip resistant: Dry: EN13893>0.3 Slip resistant: Wet: DIN 51 130 R10
	Safety	Sparclean®	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Slip resistant: Dry: EN13893>0.3 Slip resistant: Wet: DIN 51 130 R10
	Multilayered	Protectsol®	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Durable K5 wear rating Abrasion Group T to EN 649 Sound insulation: EN ISO 717-2 17db
	Multilayered	Protectsol®	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Durable K5 wear rating Abrasion Group T to EN 649 Sound insulation: EN ISO 717-2 17db
	Multilayered	Protectsol®	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Durable K5 wear rating Abrasion Group T to EN 649 Sound insulation: EN ISO 717-2 17db
	Multilayered	Protectsol®	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Durable K5 wear rating Abrasion Group T to EN 649 Sound insulation: EN ISO 717-2 17db
	Multilayered	Protectsol®	2.0mm	2.0mm	2700g/m ²	2 x 20m	2 x 20m	Durable K5 wear rating Abrasion Group T to EN 649 Sound insulation: EN ISO 717-2 17db
	Multilayered/Comfort	Tarayal Comfort****	3.2mm	0.65mm	2300g/m ²	1.5 x 30m	50 x 50cm	Ultra low maintenance – no polishes required
	Multilayered/Comfort	Tarayal Comfort****	3.2mm	0.65mm	2300g/m ²	1.5 x 30m	50 x 50cm	Ultra low maintenance – no polishes required
	Multilayered/Comfort	Tarayal Comfort	3.0mm	0.7mm	2815g/m ²	2 & 4 x 20m	50 x 50cm	Ultra low maintenance – no polishes required
	Multilayered/Comfort****	Nera Contract	2.2mm	0.7mm	2815g/m ²	2 & 4 x 20m	50 x 50cm	Ultra low maintenance – no polishes required
	Multilayered	Nera Contract	2.2mm	0.7mm	2815g/m ²	2 & 4 x 20m	50 x 50cm	Ultra low maintenance – no polishes required

*For high contamination areas e.g. Commercial kitchens, Gerflor recommends Tarasafe Super which has a slip resistance of R11 when wet in accordance with DIN 51 130. ** GTI is also available in an Anti-static version in accordance with EN 1815 and offers a noise reduction of 18db to EN 717/2. **** The Taralay Impressions range is available from 2006. Some references will be available with a Comfort foam backing on some references available in Multi-layered format too.