

## DESCRIPTION

We maintain only the highest standards in the materials, production techniques and quality control measures used to manufacture our fasteners, assuring consistent, optimum quality in every fastener.

### FASTENER TERMINOLOGY SUFFIX

K = Knurled      X = Collated      C = 100 count  
 B = Black      SD = Washer      M = 1000 count  
 E = Ramguard

## ADVANTAGES

### BLACK PINS

The special black coating improves pin penetration into difficult base material (i.e. hard concrete). We offer this black coating on all of our fasteners manufactured for the attachment of drywall track and channel to concrete and steel.

### PINS

ITW Ramset powder actuated fasteners are specifically fabricated to meet the exacting requirements of toughness and durability that enable them to penetrate dense concrete and structural quality steel.

## Selection Charts

### BLACK TRACK PINS *Designed for use in concrete and structural steel applications*

AVAILABLE IN 100-PACK OR 1000-PACK PER BOX.



PART NUMBER	SHANK LENGTH IN.	SHANK LENGTH (MM)	721	AUTO FAST	D60	SA270	ROCKET/ D45A	COBRA	RS22/ HD22
1506B	3/4	(19.1)	■	■	■	■	■	■	■
<i>Shank diameter = .145</i>									
<i>Head diameter = .300</i>									

### DRIVE PINS *Designed for use in concrete and structural steel applications*

100 PER BOX.



PART NUMBER	SHANK LENGTH IN.	SHANK LENGTH (MM)	721	AUTO FAST	D60	SA270	ROCKET/ D45A	COBRA	RS22/ HD22
1503K	1/2 Knurled	(12.7)	■	■	■	■	■	■	■
1506	3/4	(19.1)	■	■	■	■	■	■	■
1508	1	(25.4)	■	■	■	■	■	■	■
1510	1-1/4	(31.8)	■	■	■	■	■	■	■
1512	1-1/2	(38.1)	■	■	■	■	■	■	■
1514	2	(50.8)		■	■	■	■	■	■
1516	2-1/2	(63.5)		■		■		■	■
1524	3	(76.2)				■			■
<i>Shank diameter = .145</i>									
<i>Head diameter = .300</i>									