

Accessories Selection Chart



ONE HOLE CONDUIT STRAP

Used to attach conduit or armored cable to concrete.

POWERPOINT FASTENER PREASSEMBLED TO A 16 GAUGE CONDUIT STRAP. 100 PER BOX. MASTER CARTON 5 BOXES.

FITS D60, VIPER, ROCKET AND COBRA

PART NUMBER	DESCRIPTION
38HSS10	3/8" Hole strap with 1" premium pin
12HSS10	1/2" Hole strap with 1" premium pin
34HSS10	3/4" Hole strap with 1" premium pin
10HSS10	1" Hole strap with 1-1/4" premium pin

Shank diameter = .125 / .150 Head diameter = .300
38HSS10 = 18 gauge



CEILING CLIP ASSEMBLIES

Designed for suspended ceilings and other overhead applications.

PIN PREASSEMBLED TO A 14 GAUGE ANGLE CLIP. 1000 PER BOX.

FITS D60, VIPER, ROCKET AND COBRA

PART NUMBER	PIN LENGTH IN.	(MM)
SDC100	1	(25.4)
SDC125*	1-1/4	(31.8)

*Available in 100-Pack (part number SDC125C)
Shank diameter = .145 Head diameter = .300

THREADED ROD HANGER

For suspended ceilings, piping and other items using 1/4" or 3/8" threaded rod.

POWERPOINT FASTENER IS PREASSEMBLED TO A 16 GAUGE THREADED ROD HANGER. 100 PER BOX. MASTER CARTON 5 BOXES.

FITS D60, VIPER, ROCKET AND COBRA

PART NUMBER	DESCRIPTION
14TRHSS10	1/4" Rod hanger with 1" premium pin
38TRHSS10	3/8" Rod hanger with 1" premium pin

Shank diameter = .125 / .150 Head diameter = .300

THREADED STUD

For applications that require removability or where shimming is required.

1/4-20 THREADED STUD. 100 PER BOX. MASTER CARTON 10 BOXES.

FITS D60, VIPER, ROCKET AND COBRA

PART NUMBER	THREAD LENGTH IN.	(MM)	SHANK LENGTH IN.	(MM)
1623WK	3/4	(19.1)	1/2 Knurled	(12.7)
1643W	3/4	(19.1)	1	(25.4)

Shank diameter = .145
Use 1623WK for Steel Base Materials Use 1643W for Concrete Base Materials



CONDUIT CLAMP

Used to attach conduit to concrete.

POWERPOINT PIN PREASSEMBLED TO AN 18 GAUGE CONDUIT CLAMP. 50 PER BOX. MASTER CARTON 5 BOXES.

FITS VIPER

PART NUMBER	DESCRIPTION
12CCSS10L	1/2" Conduit clamp with 1" premium pin
34CCSS10L	3/4" Conduit clamp with 1" premium pin
12CCMPO34L	1/2" Conduit clamp with 3/4" plated pin
34CCMPO34L	3/4" Conduit clamp with 3/4" plated pin

Shank diameter = .125 / .150 Head diameter = .300



POWERPOINT PINS WITH CEILING CLIPS

Designed for difficult overhead applications.

PIN PREASSEMBLED TO A 14 GAUGE ANGLE CLIP. 1000 PER BOX.

FITS D60, VIPER, ROCKET AND COBRA

PART NUMBER	PIN LENGTH IN.	(MM)
SPC78	7/8	(22.2)
SPC114	1-1/4	(31.8)

Shank diameter = .150 (SPC114 = .150 / .180) Head diameter = .300



TOP HAT DRIVE PIN

Increases bearing surface against material to be fastened for improved attachment to inconsistent base materials.

100 PER BOX. MASTER CARTON 50 BOXES.

FITS D60, ROCKET AND COBRA

PART NUMBER	SHANK LENGTH IN.	(MM)
SP58TH	5/8	(15.9)
1906	3/4	(19.1)
1908	1	(25.4)

Shank diameter = .145 (SP58TH = .150)
Head diameter = 8mm (SP58TH = .300)



FASTENER ANGLE CLIP

General purpose 3/4" wide angle clip.

14 GAUGE ANGLE CLIP. 100 CLIPS PER BOX. MASTER CARTON 10 BOXES.

PART NUMBER	DESCRIPTION
1202CF	Angle clip (no pin)

Hole diameter: 5/16" and 13/64"



Commonly Used Pins Selection Chart

ADVANTAGES

PINS

ITW Ramset powder actuated fasteners are specifically fabricated to meet the exacting requirements of toughness and durability that enable them to penetrate dense concrete and structural quality steel.

BLACK PINS

The special black coating improves pin penetration into difficult base material (i.e. hard concrete). We offer this black coating on all of our fasteners manufactured for the attachment of drywall track and channel to concrete and steel.

We maintain only the highest standards in the materials, production techniques and quality control measures used to manufacture our fasteners, ensuring consistent, optimum quality in every fastener.

FASTENER TERMINOLOGY SUFFIX

K = Knurled B = Black SD = Washer

BLACK TRACK PINS

Designed for use in concrete and structural steel applications.

1000-PACK PER BOX. MASTER CARTON 5 BOXES.

FITS D60, ROCKET AND COBRA

PART NUMBER	SHANK LENGTH	
	IN.	(MM)
1506B	3/4	(19.1)

Shank diameter = .145 Head diameter = .300



DRIVE PINS

Designed for use in concrete and structural steel applications. Fasten electrical boxes or anything flat to 1/4" steel or concrete.

100 PER BOX. MASTER CARTON 50 BOXES.

FITS D60, ROCKET AND COBRA

PART NUMBER	SHANK LENGTH	
	IN.	(MM)
1503K	1/2 Knurled	(12.7)
1506	3/4	(19.1)
1508	1	(25.4)
1510*	1-1/4	(31.8)

Shank diameter = .145 Head diameter = .300
 * Master carton 10 boxes.



DRIVE PINS WITH WASHER

Washer increases bearing surface against the material to be fastened.



16 GAUGE METAL WASHER. 100 PER BOX. MASTER CARTON 10 BOXES.

FITS D60, ROCKET AND COBRA

PART NUMBER	SHANK LENGTH	
	IN.	(MM)
1506SD	3/4	(19.1)
1508SD	1	(25.4)
1510SD	1-1/4	(31.8)
1512SD	1-1/2	(38.1)

Shank diameter = .145 Head diameter = .300

POWERPOINT PINS

Used for fastening into harder steel and concrete. Premium steel and hard concrete pin.



100 PER BOX. MASTER CARTON 50 BOXES.

FITS D60, ROCKET AND COBRA

PART NUMBER	SHANK LENGTH	
	IN.	(MM)
SP12	1/2	(12.7)
SP58	5/8	(15.9)
SP34	3/4	(19.1)
SP78	7/8	(22.2)

Shank diameter = .150 Head diameter = .300

POWERPOINT STEP SHANK PINS

Used for fastening into harder steel and concrete. Premium steel and hard concrete pin.



PIN FOR FASTENING INTO HARDER STEEL AND CONCRETE. 100 PER BOX. MASTER CARTON 50 BOXES.

FITS D60, ROCKET AND COBRA

PART NUMBER	SHANK LENGTH	
	IN.	(MM)
SP100	1	(25.4)

Shank diameter = .150 / .180 Head diameter = .300

M100BB PIN

For general purpose attachments to concrete.



POWERPOINT STEP SHANK PIN PREASSEMBLED TO 1/2" WASHER. 500 PER BOX. MASTER CARTON 5 BOXES.

FITS ALL POWDER TOOLS AND SINGLE PIN GAS TOOLS

PART NUMBER	DESCRIPTION
M100BB	1" PowerPoint step shank pin with 1/2" domed washer and flute

Shank diameter = .125 / .150 Head diameter = .300

