

ARDEX K 15 Self-Leveling Underlayment Concrete

Portland cement-based, high-strength, fast-setting, non-shrinking underlayment. Mix with water, pour or pump, spread, ready!

Product Capabilities:

For use over concrete, metal, terrazzo, ceramic tile, wood and non-water-soluble old flooring adhesive residue (including cutback), on, above or below grade.

Pourable or pumpable. Installs from featheredge to 1-1/2" in one operation; up to 5" with the addition of proper aggregate. Designed specifically for fast leveling of floors, ARDEX K 15 provides a durable, flat and smooth floor surface with minimum labor and installation time.

ARDEX K 15 hardens quickly by hydration and drying. It will not shrink, crack or spall, even when applied in thick layers. Floor coverings can be installed just 16 hours later.

ARDEX K 15 is recommended and specified by most flooring manufacturers, architects, and contractors.

Benefits:

- Portland cement based
- High strength - 4100 psi
- Installs up to 5" thick
- Designed specifically for fast leveling of floors
- Use to level and smooth interior concrete, terrazzo, quarry and ceramic tile, cutback adhesive residue (non-water-soluble), wood, and metal
- Walk on in 2-3 hours
- Install floor covering after 16 hours

Click Below for Technical and Specification Documents:

[Tech Info & Installation \(English\)](#)

