

Selection Charts

COLLATED POWDER ACTUATED DRIVE PINS Designed for high volume repetitive fastenings to concrete and steel

FASTENERS COLLATED 10 PER STRIP. 100 STRIPS PER BOX.



| SHANK | LENGTH |
|-------|------------|
| IN. | (MM) |
| 5/8 | (15.9) |
| 3/4 | (19.1) |
| 1-1/4 | (31.8) |
| | 5/8 3/4 |

Shank diameter = .145, SP58X = .150Head diameter = .300

Fits many competitive powder actuated tools with fastener magazines

DRIVE PINS WITH WASHER Washer increases bearing surface against the material to be fastened

100 PER BOX. 16 GAGE METAL WASHER



| PART | SHANKL | .ENGTH | | AUTO | | | ROCKET/ | , | RS22/ |
|----------|--------|--------|------------|------|------------|-------|---------|-------|-------|
| NUMBER | IN. | (MM) | 721 | FAST | D60 | SA270 | D45A | COBRA | HD22 |
| 1506SD | 3/4 | (19.1) | - | | | | | - | |
| 1508SD | 1 | (25.4) | | | | | | | |
| 1510SD | 1-1/4 | (31.8) | | | | | | | |
| 1512SD | 1-1/2 | (38.1) | | | | | | | |
| 1514SD | 2 | (50.8) | | | | | | | |
| 1516SDC | 2-1/2 | (63.5) | | | | | | | |
| 1524SDP* | 3 | (76.2) | | | | | | - | |

*Square washer indicates 3" pin has been installed

Shank diameter = .145 $Head\ diameter = .300$

Head diameter = .300

POWERPOINT PINS Used for fastening into harder steel and concrete. Premium steel and hard concrete pin

100 PER BOX.



| | PART | SHANK | LENGTH | | AUTO | | | ROCKET/ | , | RS22/ |
|---|----------------|-------|--------|------------|------|------------|--------------|---------|--------------|-------|
| | NUMBER | IN. | (MM) | 721 | FAST | D60 | SA270 | D45A | COBRA | HD22 |
| | SP12 | 1/2 | (12.7) | | | | | | | |
| | SP58 | 5/8 | (15.9) | | | | | | | |
| | SP34 | 3/4 | (19.1) | | | | | | | |
| ĺ | SP78 | 7/8 | (22.2) | | | | | | | |
| | Shank diameter | =.150 | | | | | | | | |

POWERPOINT STEP SHANK PINS Used for fastening into harder steel and concrete. Premium steel and hard concrete pin

PIN FOR FASTENING INTO HARDER STEEL AND CONCRETE. 100 PER BOX.



| PART | SHANK L | ENGTH |
|--------|---------|--------|
| NUMBER | IN. | (MM) |
| SP100 | 1 | (25.4) |
| SP114 | 1-1/4 | (31.8) |
| SP112 | 1-1/2 | (38.1) |
| SP178 | 1-7/8 | (47.6) |

Shank diameter = .150 / .180 $Head\ diameter = .300$

| AUTO | | | ROCKET/ | , | RS22/ | |
|------|------------|-------|---------|-------|-------|--|
| FAST | D60 | SA270 | D45A | COBRA | HD22 | |
| | | - | | - | | |
| | | - | | - | | |
| | | - | | - | | |
| | | | | | | |