

# RL510



**The RL510 is a fully automatic rotating laser** that can be used for leveling, vertical alignment, plumbing and squaring. Applications include installing suspended ceilings, soffits, stud & track layout and a variety of interior alignment tasks.

**LONGER LIFE**

**160 hours on two D alkalines  
40 hours on rechargeable NiCad**  
(both battery options are included)

**SAVE TIME**

**Built in WALL MOUNT**  
**virtually eliminates setup**

**SEE THE LIGHT**

**Laser target allows you to use in  
high ambient light applications**

**HANDS FREE**

**Remote allows you to adjust the  
laser from where you work**



## Advanced Features

- Integrated motorized wall mount adjustable by remote control
- Automatic self leveling in both horizontal and vertical modes
- Manual leveling mode for slopes or inclined planes
- Choice of beams:
  - ROTATING
  - SCANNING
  - CHALK LINE
- Easy field calibration.

**RL510 Interior Kit**  
includes, rotating laser,  
integrated motorized wall  
mount, rechargeable and  
alkaline battery packs  
remote control, target  
card, laser enhancing  
glasses, and impact  
resistant carrying case.

**Operation**

The RL510 is self leveling in vertical and horizontal applications and fully controllable by the included remote control. The laser is on automatic mode once it is turned on; it will pause for a few seconds to level itself then begin rotating. Once it's level modes can be changed to suit your application. If the laser is moved it will pause while it levels itself again then continue rotating.





RL510



DW077K



HV101



PR12



HV301



PR25

	Part No.	RL510	DW077K	HV101	HV301	PRI 2	PR25
Manufacturer	Ramset	DeWalt	Spectra	Spectra	Hilti	Hilti	
<b>Accuracy @ 100 ft Range</b>	1/8"	1/8"	1/8'	3/32"	1/8"	1/11"	
<b>Battery Life (Alkaline)</b>	160 hrs	na	50 hrs	90 hrs	<50 hrs	50 hrs	
<b>Battery Life (Rechargeable)</b>	40 hrs	8 hrs <sup>1</sup>	na <sup>2</sup>	40 hrs	<40 hrs	40 hrs	
<b>Self Leveling Range (Horizontal)</b>	±10 deg	±5 deg	±5 deg	±5 deg	±5 deg	±5 deg	±5 deg
<b>Self Leveling Range (Vertical)</b>	±10 deg	±5 deg	±5 deg	±5 deg	±5 deg	±5 deg	±5 deg
<b>Wall Mount</b>	Integrated	no <sup>3</sup>	no <sup>3</sup>	no <sup>3</sup>	no <sup>3</sup>	no <sup>3</sup>	no <sup>3</sup>
<b>Motorized Wall Mount</b>	Integrated	na	na	na	na	na	na
<b>Field Calibrateable</b>	Yes	no <sup>4</sup>	no <sup>4</sup>	no <sup>4</sup>	no <sup>4</sup>	no <sup>4</sup>	no <sup>4</sup>
<b>Chalk Line Mode</b>	Yes	Yes	na	na	na	na	na
<b>Scan Mode</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Manual Slope Mode</b>	Yes	na	Yes	Yes	Yes	Yes	Yes
<b>Alkaline "D" Battery Capable</b>	Yes	na	Yes	Yes	Yes	Yes	Yes
<b>Rechargeable Battery</b>	Yes	Yes	no <sup>3</sup>	Yes	no <sup>3</sup>	no <sup>3</sup>	no <sup>3</sup>
<b>Remote Control</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes

RL510 Interior Kit includes,  
 rotating laser, integrated  
 motorized wall mount,  
 rechargeable and alkaline  
 battery packs remote control,  
 target card, laser enhancing  
 glasses, and impact resistant  
 carrying case.



1. With 18V DeWalt battery.

2. With "user provided Ni-MH/Ni-CD batteries."

3. Not included with base model. Must be purchased with optional interior kit.

4. Requires professional calibration performed by qualified service center.