

HENRY®



440

High-performance wet-set adhesive for installing rubber and vinyl cove base

- Aggressive Initial Grab**
Prevents slip during installation
- No Open Time Required**
For quicker installation
- Plasticizer Migration-Resistant**
For installing vinyl cove base
- Easy Cleanup**
With water
- Excellent Trowelability**
Easy to use, easy to trowel
- AGIS Guarantee**
Included as part of Armstrong Guaranteed Installation System when installing Armstrong rubber and vinyl cove base

Sizes Available
11oz., 30 oz., 1 quart, 1 gallon, 4 gallon



THE PROFESSIONAL'S FORMULA FOR SUCCESS™

HENRY® 440

HENRY 440 is The Professional's Formula For Success when installing either rubber or vinyl cove base.

| | HENRY 440 | HENRY 595 |
|------------------|-----------|-----------|
| COVE BASE | | |
| Rubber Cove Base | BEST | BEST |
| Vinyl Cove Base | BEST | BEST |

SUBSTRATES:

HENRY 440 Cove Base Adhesive may be used over:

- Structurally sound, clean, smooth, and dry wall surfaces
- Glazed or metal surfaces should be abraded

INSTALLATION TIPS:

- Condition the area to be installed, adhesive, and cove base to 65°F (18°C) or above for 48 hours before, during, and for 48 hours after installation.
- Walls must be smooth, sound, dry, clean, and free of dirt, wax, polish, paint, and all other foreign matter that may interfere with a good bond.
- Stir any liquid on the surface into the adhesive and apply using the recommended trowel.
- Apply adhesive to the back of the cove base or to the wall. Stay 1/8" away from top of cove base to prevent adhesive oozing.
- Place cove base into position. Butt joints neatly.
- Using a hand roller, roll toward the previously installed section.



RUBBER OR VINYL COVE BASE
 SAWTOOTH 1/8D x 1/8W
 310-340 lin ft/gal - 2 1/2" Cove Base
 220-240 lin ft/gal - 4" Cove Base
 165-180 lin ft/gal - 6" Cove Base

HENRY

The W. W. Henry Company
 400 Ardex Park Drive
 Aliquippa, PA 15001
 Technical Support: 1-800-232-4832
 Internet: wwhenry.com

HENRY Commitment

HENRY is committed to helping you get the best results in professionally installed floors. Sixty years of experience combined with our relationships with the leading resilient, wood and carpet manufacturers ensure that you receive the products and the support you need to complete the job successfully and profitably.

IPD-242-899

THE PROFESSIONAL'S FORMULA FOR SUCCESS™