

Fabricwal®

10650/PAN
BuyLine 7239



Panelfold®
1953-2003

Soft Covered Accordion Partitions

Fabricwal® Soft Covered Accordion Partitions




Panelfold's Fabricwal Accordion Partitions combine the best features of the other popular brands of fabric accordion partitions with added timely innovations. Sight dividing models as well as acoustically rated models may be specified.

- Sound ratings of STC 39 and STC 40
- Steel pantograph framework
- Exclusive adjustable sweepseals
- Vinyl, fabric, or carpet covers



AIR RELEASE vents allow air trapped during the operation of the partition to escape for easier operation. Gripull handles and positive latches are standard.

TYPES OF APPLICATIONS



For complete details and specifications, see Product Briefs, Interactive CD-ROM or Panelfold website at www.panelfold.com

GUIDE SPECIFICATIONS

PART 2. PRODUCTS

2.1 ACCORDION PARTITION shall be (specify: Fabricwal non-acoustical; STC 39; or STC 40); (specify: manually or electrically operated) as manufactured by Panelfold, Inc., Miami, Florida, USA.

2.2 ACOUSTICAL TREATMENT: Continuous vinyl sweep seal installed both sides, fixed at top and adjustable at bottom; formed steel insulating panels, continuously lined with acoustical membrane; deep-nesting end posts with sound seals; and positive latch. Partitions shall be as independently tested in accordance with ASTM E90-85.

2.3 FRAMEWORK shall be formed 16 gauge steel pantograph hinge plates welded to 3/16" diameter steel rods. Install a single row top and bottom at 42" intervals of height. Install double row at top over 12'1" high. Steel alloy carrier pendant shall be suspended from reinforced hinge channel.

2.4 COVERS of heavy duty, Class "A" flame spread rated vinyl with 100% polyester backing or covers of wall carpet or panel fabrics shall be steel leaf fastened to the frame. Colors to be selected from manufacturer's standards


2.5 TRACK shall be heavy duty extruded aluminum (with integral Ceilingshield™ for recessed track applications). Two ball-bearing wheels shall be installed at every other volute and four wheels at each end post.

2.6 END POSTS of fabric or carpet covered 16 gauge (1.6mm) formed steel shall have deep-nesting natural anodized aluminum nose with 3/8" (10mm) diameter holes to release trapped air; Gripull™ handles, automatic latches and jamb mould.

2.7 STACK FORMULA: (Approx.) 2"/ft. (167mm/m) plus 4" (102mm) for each end post.

2.8 HANGING WEIGHT: (Approx.) Non-acoustical 2.0 lbs./ft² (10kg/m²); STC 39, 5.0 lbs./ft² (23kg/m²); STC 40, 5.5 lbs./ft² (27kg/m²).

VERTICAL SECTION - HEAD DETAILS



All Dimensions Shown in Parentheses are Millimeters



Panelfold® Surfaces & Colors

You may select from an extensive line of surfaces and colors. Color selectors are available.

WOOD VENEERS



WHITE ASH



NATURAL BIRCH



RED OAK



AMERICAN WALNUT

WOODTEX WOOD GRAIN VINYL



WHEATWOOD™



HONEYWOOD™



CANYONWOOD™



SABLEWOOD™

STARTEX™ TEXTURED VINYL



WHITE



ROSE MIST



OYSTER



CLOUD

SANDTEX™ MULTICOLOR VINYL



OYSTER



GREIGE



EARLY SKY



MORNING MIST



DOVER



CORAL SAND



PEARL



SEA FOAM

FABRICTEX FABRIC TEXTURED VINYL



ROPETEX ROPE TEXTURED VINYL



SNOW DRIFT



FROSTY



TAUPE



CLOUD

HIGHTEX™ HIGHLY TEXTURED VINYL



CLOUD



FAWN



ANTIQUE ROSE



CEMENT

RIBTEX BASIC™ VERTICAL RIB WALL CARPET



MALIBU



BUCKSKIN



SAND



TAUPE



CLOUD



FLINT



MEADOW



CARNIVAL

WOVENTEX® I & II PANEL FABRICS



ROSE



BRITTANY



ORCHID



TWILIGHT

WOVENTEX® III PANEL FABRICS



BURNISH



LILAC



SUN DRENCHED



MORRIS CODE

TEK-WALL® 1000® PANEL FABRICS



BISCUIT BEIGE



WOODROSE PETAL



PEBBLE BEACH




SPRAY MIST



In colors to blend or contrast with panel finish. Color selection card is available.

WILSON ART® OR FORMICA® DECORATIVE LAMINATES




SANIBEL MAPLE



SHERIL WALNUT



WINDSOR MAHOGANY



CASHMERE



STORM NEBULA

For color selections, see Selectors, Interactive CD-ROM or Panelfold website at www.panelfold.com