TANK ALERT® 4X Alarm System

Easy-to-install liquid level alarm system which has a NEMA 4X enclosure for indoor or outdoor use.

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other non-potable water applications.

The Tank Alert® 4X alarm system can serve as a high or low level alarm depending on the float switch model used.

The stainless steel alarm horn sounds and red beacon illuminates when a potentially threatening liquid level condition occurs.



FEATURES

- NEMA 4X enclosure rated for indoor or outdoor use.
- Automatic alarm reset and alarm test/normal/silence switch.
- Alarm system (when installed on separate circuit) operates even if the pump circuit fails.
- Complete package includes standard SJE SignalMaster® control switch with 15 feet (4.57 meters) of cable (other lengths available) and mounting clamp.
- UL/_cUL Listed.
- Three-year limited warranty.





OPTIONS

When ordered with the alarm, this system is available with:

- alternate float switch models for high or low level warning.
- auxiliary dry contacts (normally open and normally closed) for easy attachment of remote devices.

SPECIFICATIONS

VOLTAGE FOR <u>120 VAC</u> MODEL: 120 VAC, 50/60 Hz

ALARM ENCLOSURE: 6.4 x 5.3 x 5 inch (16.2 x 13.5 x 13.34 cm), NEMA 4X, indoor-outdoor, weatherproof, UV stabilized thermoplastic

ALARM HORN: 88 decibels at 10 feet (3 meters)

ALARM BEACON: UL Listed, Type 4X beacon assembly

AUXILIARY ALARM CONTACTS
(OPTIONAL): 120 VAC, 5 amps max.,
50/60 Hz

FLOAT SWITCH: SJE SignalMaster® control switch with mounting clamp

Cable: 15 feet (4.57 meters), flexible 18 gauge, 2 conductor (UL) SJOW, waterresistant (CPE)

Float: 2.74 inch diameter x 4.83 inch long (7 cm x 12.3 cm), high impact, corrosion resistant polypropylene housing for use in sewage and non-

potable water up to 140°F (60°C) **Maximum Water Depth:** 30 feet (9 meters), 13 psi

Electrical: 5 amps, 125 VAC/250 VAC, 50/60 Hz



PO Box 1708, Detroit Lakes, MN 56502 1-888-DIAL-SJE • 1-218-847-1317 1-218-847-4617 Fax

email: sje@sjerhombus.com **www.sjerhombus.com**