


**SPECIFICATION:** BLÜCHER PIPE AISI Type 316L (standard) stainless steel pipe system, with Push-Fit socket connections with EPDM (standard) sealing ring. All BLÜCHER PIPE to be treated with pickling and passivation finish process.



#### Dimensional Chart

Model No.	D	X	Weight Lbs.
P2-0.5-316	2"(50)	5-7/8"(150)	0.7(0.3)
P2-0.8-316	2"(50)	9-13/16"(250)	0.9(0.4)
P2-1.6-316	2"(50)	1'-7-11/16"(500)	1.5(0.7)
P2-2.5-316	2"(50)	2'-5-1/2"(750)	2.2(1.0)
P2-3.3-316	2"(50)	3'-3-3/8"(1000)	2.9(1.3)
P2-4.9-316	2"(50)	4'-11-1/8"(1500)	4.2(1.9)
P2-6.6-316	2"(50)	6'-6-11/16"(2000)	5.5(2.5)
P2-9.8-316	2"(50)	9'-10-1/8"(3000)	8.4(3.8)
P2-13.1-316	2"(50)	13'-1-7/16"(4000)	11.2(5.1)
P2-16.4-316	2"(50)	16'-4-7/8"(5000)	13.9(6.3)
P2-19.7-316	2"(50)	19'-8-1/4"(6000)	16.8(7.6)
P3-0.5-316	3"(75)	5-7/8"(150)	0.9(0.4)
P3-0.8-316	3"(75)	9-13/16"(250)	1.3(0.6)
P3-1.6-316	3"(75)	1'-7-11/16"(500)	2.2(1.0)
P3-2.5-316	3"(75)	2'-5-1/2"(750)	3.3(1.5)
P3-3.3-316	3"(75)	3'-3-3/8"(1000)	4.4(2.0)
P3-4.9-316	3"(75)	4'-11-1/8"(1500)	6.2(2.8)
P3-6.6-316	3"(75)	6'-6-11/16"(2000)	8.2(3.7)
P3-9.8-316	3"(75)	9'-10-1/8"(3000)	12.8(5.8)
P3-13.1-316	3"(75)	13'-1-7/16"(4000)	17.0(7.7)
P3-16.4-316	3"(75)	16'-4-7/8"(5000)	20.1(9.5)
P3-19.7-316	3"(75)	19'-8-1/4"(6000)	25.1(11.4)
P4-0.5-316	4"(110)	5-7/8"(150)	1.3(0.6)
P4-0.8-316	4"(110)	9-13/16"(250)	2.0(0.9)
P4-1.6-316	4"(110)	1'-7-11/16"(500)	3.3(1.5)
P4-2.5-316	4"(110)	2'-5-1/2"(750)	4.9(2.2)
P4-3.3-316	4"(110)	3'-3-3/8"(1000)	6.4(2.9)
P4-4.9-316	4"(110)	4'-11-1/8"(1500)	9.5(4.3)
P4-6.6-316	4"(110)	6'-6-11/16"(2000)	11.9(5.4)
P4-9.8-316	4"(110)	9'-10-1/8"(3000)	18.3(8.3)
P4-13.1-316	4"(110)	13'-1-7/16"(4000)	24.9(11.3)
P4-16.4-316	4"(110)	16'-4-7/8"(5000)	30.9(14.0)
P4-19.7-316	4"(110)	19'-8-1/4"(6000)	37.0(16.8)

#### Dimensional Chart Continued

Model No.	D	X	Weight Lbs.
P5-0.5-316	5"(125)	5-7/8"(150)	1.5(0.7)
P5-0.8-316	5"(125)	9-13/16"(250)	2.2(1.0)
P5-1.6-316	5"(125)	1'-7-11/16"(500)	4.0(1.8)
P5-2.5-316	5"(125)	2'-5-1/2"(750)	5.7(2.6)
P5-3.3-316	5"(125)	3'-3-3/8"(1000)	7.3(3.3)
P5-4.9-316	5"(125)	4'-11-1/8"(1500)	10.8(4.9)
P5-6.6-316	5"(125)	6'-6-11/16"(2000)	14.1(6.4)
P5-9.8-316	5"(125)	9'-10-1/8"(3000)	20.9(9.5)
P5-13.1-316	5"(125)	13'-1-7/16"(4000)	27.8(12.6)
P5-16.4-316	5"(125)	16'-4-7/8"(5000)	34.4(15.6)
P5-19.7-316	5"(125)	19'-8-1/4"(6000)	41.2(18.7)
P6-0.5-316	6"(160)	5-7/8"(150)	2.7(1.2)
P6-0.8-316	6"(160)	9-13/16"(250)	3.8(1.7)
P6-1.6-316	6"(160)	1'-7-11/16"(500)	6.6(3.0)
P6-2.5-316	6"(160)	2'-5-1/2"(750)	9.3(4.2)
P6-3.3-316	6"(160)	3'-3-3/8"(1000)	12.1(5.5)
P6-4.9-316	6"(160)	4'-11-1/8"(1500)	17.6(8.0)
P6-6.6-316	6"(160)	6'-6-11/16"(2000)	23.2(10.5)
P6-9.8-316	6"(160)	9'-10-1/8"(3000)	34.4(15.6)
P6-13.1-316	6"(160)	13'-1-7/16"(4000)	45.4(20.6)
P6-16.4-316	6"(160)	16'-4-7/8"(5000)	56.7(25.7)
P6-19.7-316	6"(160)	19'-8-1/4"(6000)	67.7(30.7)
P8-0.5-316	8"(200)	5-7/8"(150)	4.4(2.0)
P8-0.8-316	8"(200)	9-13/16"(250)	6.2(2.8)
P8-1.6-316	8"(200)	1'-7-11/16"(500)	10.1(4.6)
P8-2.5-316	8"(200)	2'-5-1/2"(750)	14.3(6.5)
P8-3.3-316	8"(200)	3'-3-3/8"(1000)	18.3(8.3)
P8-6.6-316	8"(200)	6'-6-11/16"(2000)	34.6(15.7)
P8-9.8-316	8"(200)	9'-10-1/8"(3000)	50.9(23.1)
P10-1.6-316	10"(250)	1'-7-11/16"(500)	12.8(5.8)
P10-3.3-316	10"(250)	3'-3-3/8"(1000)	23.2(10.5)
P10-6.6-316	10"(250)	6'-6-11/16"(2000)	43.4(19.7)
P10-9.8-316	10"(250)	9'-10-1/8"(3000)	63.9(29.0)

Job Name \_\_\_\_\_ Contractor \_\_\_\_\_

Job Location \_\_\_\_\_ Approval \_\_\_\_\_

Engineer \_\_\_\_\_ Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_ Representative \_\_\_\_\_

