

McElroy 2-Jaw &4-Jaw DynaMc<sup>™</sup> 412 HP

## DynaMc<sup>™</sup> ↓

 McElroy 2-Jaw

 DynaMc<sup>™</sup> 412 HP

 will butt fuse all pipe sizes from

 4" IPS - 12" DIPS

 (100mm - 340mm)

 L 27.7" (704 mm)

 W 31.7" (805 mm)

 H 26.5" (673 mm)

 WEIGHT

 200 lbs (90 Kg) with cradle

 186 lbs (84 Kg) without cradle

McElroy 4-Jaw DynaMc<sup>тм</sup> 412 HP will butt fuse all pipe sizes from 4" IPS - 12" DIPS (100mm - 340mm) L 34.7" (882 mm) W 31.7" (805 mm) H 26.5" (673 mm) WEIGHT 293 lbs (132 Kg) with cradle 277 lbs (125 Kg) without cradle


The new DynaMc<sup>TM</sup> 412 HP (Hand Pump) machine butt fuses pipe from 4" IPS to 12" DIPS (110 mm-340mm) with a hand-powered pump. The 412 HP is available in 2- and 4-Jaw models. Just like a stick of dynamite, the 412 HP is a lot of power in a small package. The unit's easy-lift cradle can be removed for easier maneuvering in tight in-ditch worksites. The 412 HP's electric facer is sturdy and powerful, with the option of being loaded from either side of the machine for improved convenience.

- Double-action hand pump and high-velocity cylinders create fast carriage speed for opens and closes during fusion process
- On four-jaw units, the full-length guide rod and unique moveable third jaw allow work in close proximity to ells and tees without the removal of the outer jaw
- Patented Centerline Guidance System
- · Serrated jaws and inserts to keep pipe from slipping during fusion process
- 1500 psi pressure capability
- ISO-compliant industrial Teflon-coated heater plates
- Powerful electric facer that can be loaded from either side
- DataLogger compatible

Detachable easy-lift cradle from improved maneuverability to and from workplace



íscò



## McElroy Fusion Equipment

1-800-345-ISCO

www.isco-pipe.com

163