


IPS Fittings Fabricated Cross



IPS Fittings Fabricated Cross							
Nominal Pipe Size (in)	DR	DR	Part #	Dimensions		Weight (lbs)	Shipping Method
				L (in)	H (in)		
2	2.375	11	ISFFCS0211IPS	8	2.5	1	FedEx
3	3.5	11	ISFFCS0311IPS	8	3	2	FedEx
4	4.5	11	ISFFCS0411IPS	11	3	5	FedEx
6	6.625	11	ISFFCS0611IPS	12	4	11	FedEx
		17	ISFFCS0617IPS	"	"	9	FedEx
8	8.625	11	ISFFCS0811IPS	26.5	6	30	FedEx
		17	ISFFCS0817IPS	"	"	20	"
10	10.75	11	ISFFCS1011IPS	31.75	7.5	50	FedEx
		17	ISFFCS1017IPS	"	"	35	"
12	12.75	07	ISFFCS1207IPS	30	8.625	103	LTL
		11	ISFFCS1211IPS	"	"	72	"
		17	ISFFCS1217IPS	"	"	49	"
14	14	07	ISFFCS1407IPS	33	9.5	137	LTL
		11	ISFFCS1411IPS	"	"	96	"
		17	ISFFCS1417IPS	"	"	65	"
16	16	07	ISFFCS1607IPS	36	10	193	LTL
		11	ISFFCS1611IPS	"	"	135	"
		17	ISFFCS1617IPS	"	"	91	"
18	18	09	ISFFCS1809IPS	40	11	226	LTL
		11	ISFFCS1811IPS	"	"	190	"
		17	ISFFCS1817IPS	"	"	127	"
20	20	09	ISFFCS2009IPS	52	16	378	LTL
		11	ISFFCS2011IPS	"	"	317	"
		17	ISFFCS2017IPS	"	"	213	"
22	22	09	ISFFCS2209IPS	52	15	447	LTL
		11	ISFFCS2211IPS	"	"	375	"
		17	ISFFCS2217IPS	"	"	251	"
24	24	09	ISFFCS2409IPS	54	15	545	LTL
		11	ISFFCS2411IPS	"	"	457	"
		17	ISFFCS2417IPS	"	"	307	"
28	28	11	ISFFCS2811IPS	58	15	651	LTL
		17	ISFFCS2817IPS	"	"	437	"
30	30	11	ISFFCS3011IPS	60	15	764	LTL
		17	ISFFCS3017IPS	"	"	513	"
32	32	11	ISFFCS3211IPS	62	15	889	LTL
		17	ISFFCS3217IPS	"	"	597	"
36	36	11	ISFFCS3611IPS	72	18	1321	LTL
		17	ISFFCS3617IPS	"	"	887	"



IPS
HDPE
Fittings

Pressure Rating of Fab Cross is based pipe DR (Wall thickness) and resin properties.

Crosses from 3608 resin:	
DR	Pressure Rating
7	107 psi
9	80 psi
11	64 psi
13.5	51 psi
15.5	44 psi
17	40 psi
21	32 psi
26	26 psi
32.5	20 psi

Crosses from 4710 resin:	
DR	Pressure Rating
7	134 psi
9	101 psi
11	81 psi
13.5	64 psi
15.5	56 psi
17	50 psi
21	40 psi
26	32 psi
32.5	26 psi

Note: Size/DR listings shown are commonly requested. Many DR options not listed are available. Please consult an ISCO representative for availability.

1-800-345-ISCO

www.isco-pipe.com

