

**HDPE To Ductile / Cast Iron Coupling**



**1. Standard Coupling:**

Requires no restraint, no internal stiffeners above and below ground use  
DR 9 to DR 17 for full pressure rating

**2. Restricted use coupling:**

Ductile Body-Flow Contacts Buna N Gasket  
requires pipe restraint, internal stiffeners for HDPE  
temperature range limited(35-80 degree fahrenheit)  
below ground use only

**3. Flexible Pipe Connectors:**

External: Steel and Ductile Parts Standard (SS Optional)

**4. Engineered Coupling:**

Flow Contacts Gasket: Nitrile(Buna N) or SBR(Buna S) Standard  
For gravity and DWV applications  
designed per application

**IPS**

Pipe Size	Style			
	1	2	3	4
3/4"				
1"				
1.5"				
2"	X	X	X	
3"		X	X	
4"	X	X	X	
6"	X	X	X	
8"		X	X	
10"		X	X	
12"		X	X	
14"			X	X
16"			X	X
18"			X	X
20"			X	X
22"			X	X
24"			X	X
26"				X
28"				X
30"				X
32"				X
34"				X
36"				X

**DIPS**

Pipe Size	Style			
	1	2	3	4
4"	X	X	X	
6"	X	X	X	
8"	X	X	X	
10"	X	X	X	
12"	X	X	X	
14"		X	X	X
16"		X	X	X
18"		X	X	X
20"		X	X	X
24"		X		X
30"		X		X

\*\*Chart applies to Class 100-250 AWWA Cast Iron Pipe

**Mechanical Connectors**

**1-800-345-ISCO**

**www.isco-pipe.com**

