

CAT-5 1300 EXTENDER

Extends any VGA, USB 2.0 and audio signal up to 200 feet (60 meters) with VGA distribution to two outputs, all over two CAT-5e cables




EXT-CAT5-1300

FEATURES:

- Extends any VGA signal up to 200ft (60m)
- Supports resolutions up to 1920x1200, 2K and 1080p
- Extends USB 2.0 compliant devices up to 330ft (100m)
- Local video output on the sender unit
- Rack-mountable

SPECIFICATIONS:

- Maximum Video Bandwidth: 350 MHz
- Input Video Signal: 1.2 Volts p-p
- Input Sync Signal: 5 Volts p-p (TTL)
- Horizontal Frequency Range: 15 - 70 KHz
- Vertical Frequency Range: 30 - 170 Hz
- Video In: (1) HD-15 male
- Video Out/Receiver: (2) HD-15 female
- Video Out/Sender: (1) HD-15 female
- Audio In/Out: (1) 3.5mm mini-stereo jack
- Link Connector: (2) RJ-45 Shielded
- USB Input/Output Connectors: (1) Type B/(4) Type A
- Power Supply: 5V DC
- Power Consumption per unit: 20 Watts
- Dimensions: 4.2"D x 15.1" W x 1.8"H
- Shipping Weight / Unit Weight: 7 lbs. /3 lbs.



CAT-5 1500 EXTENDER

Extends any VGA, USB 1.1 and audio signal up to 330 feet (100 meters) with VGA distribution to two outputs, all over two CAT-5e cables



EXT-CAT5-1500

FEATURES:

- Maintains up to 1920 x 1200 resolution video
- Extends USB 1.1 signals up to 330ft (100m)
- Brightness and focus adjustments for fine tuning the output signal
- Eliminates computer noise
- Stereo audio is extended for multimedia applications
- Local video output on the sender unit
- Rack-mountable

SPECIFICATIONS:

- Maximum Video Bandwidth: 350 MHz
- Input Video Signal: 1.2 Volts p-p
- Input Sync Signal: 5 Volts p-p (TTL)
- Video In: (1) HD-15 male
- Video Out/Receiver: (2) HD-15 female
- Video Out/Sender: (1) HD-15 female
- Audio Connector: (1) 3.5mm mini-stereo jack
- Link Connectors: (2) RJ-45 shielded
- USB Input/Output Connectors: (1) Type B/(2) Type A
- Power Supply per unit: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 4.2"D x 8.4" W x 1.6"H
- Shipping Weight / Unit Weight: 6 lbs. /2 lbs.



CAT-5 5000 EXTENDER

Extends any dual VGA signal with USB 1.1 and audio up to 330 feet (100 meters) over two CAT-5e cables

FEATURES:

- Maintains up to 1920 x 1200 resolution video
- Extends USB 1.1 signals up to 330 ft (100m)
- Brightness and focus adjustments for fine tuning the output signal
- Local video output on the sender unit
- Rack-mountable

SPECIFICATIONS:

- Maximum Video Bandwidth: 350 MHz
- Input Video Signal: 1.2 Volts p-p
- Input Sync Signal: 5 Volts p-p (TTL)
- Video In: (1) HD-15 male
- Video Out/Receiver: (2) HD-15 female
- Video Out/Sender: (2) HD-15 female
- Audio Connector: (1) 3.5mm mini-stereo jack
- Link Connectors: (2) RJ-45 shielded
- USB Input/Output Connectors: (1) Type B/(4) Type A
- Power Supply: 5V DC
- Power Consumption: 20 Watts (max)
- Dimensions(S): 4.2"D x 17.1" W x 1.6"H
- Dimensions(R): 4.2"D x 8.4" W x 1.6"H
- Shipping Weight / Unit Weight: 8 lbs. /3 lbs.



EXT-CAT5-5000

