

KVM SWITCHERS

EXT-DVIKVM-241DLS



2x1 DVI KVM SL/DL SWITCHER

Switch between any two computers with support for dual link or single link DVI, USB 2.0 and audio signals

SPECIFICATIONS:

- Maximum Pixel Clock: 2x165 MHz
- Input DDC Signal: 5 Volts p-p (TTL)
- Maximum Resolution: 3840x2400
- DVI Input: (2) DVI-D DL 25 pin female
- DVI Output: (1) DVI-D DL 25 pin female
- Audio Input: (2) 3.5mm mini-stereo jack
- Audio Output: (1) 3.5mm mini-stereo jack
- USB Input Connection: (2) Type B
- USB Output Connection: (2) Type A
- Rack Size: 1U (half-width)
- Power Supply: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 4.2"D x 8.4" W x 1.6"H
- Shipping Weight / Unit Weight: 1 lb /5 lbs.

FEATURES:

- Supports resolutions up to 3840x2400
- Save time and increase productivity
- Supports all major operating systems - Windows, MacOS and Linux
- Integrated 2-port USB hub
- Front panel switching
- Discrete IR remote (included)
- Contact closure remote port (RMT-2 not included)
- Supports DDWG standards for DVI monitors
- Rack-mountable

2x
Computers



KVM

EXT-DVI-441DLP



4x1 DVI DL KVM SWITCHER

Switch between any four computers with support for dual link DVI, USB 2.0 and audio signals

SPECIFICATIONS:

- Maximum Pixel Clock: 2x165 MHz
- Maximum Resolution: 3840x2400
- DVI Input: (4) DVI-D DL 24 pin female
- DVI Output: (1) DVI-D DL 24 pin female
- Audio Input: (4) 3.5mm mini-stereo jack
- Audio Output: (1) 3.5mm mini-stereo jack
- USB Input Connection: (4) Type B
- USB Output Connection: (2) Type A
- Power Consumption: 10 Watts (max)
- Rack Size: 1U (rack-ears included)
- Power Supply: 5V DC
- Dimensions: 4.2"D x 17.1" W x 1.8"H
- Shipping Weight / Unit Weight: 2 lbs. /8 lbs.

FEATURES:

- Supports resolutions up to 3840x2400
- Save time and increase productivity
- Supports all major operating systems - Windows, MacOS and Linux
- Integrated 2-port USB hub
- Discrete front panel switching
- Discrete IR remote (included)
- Contact closure remote port (RMT-4 not included)
- Parallel RS-232 control version available (EXT-DVI-441DLP)
- Supports DDWG standards for DVI monitors
- Rack-mountable

4x
Computers



KVM

EXT-DVIKVM-841DL



8x1 DVI KVM DL/SL SWITCHER

Switch between any eight computers with support for dual link or single link DVI, USB 2.0 and audio signals

SPECIFICATIONS:

- Maximum Pixel Clock: 2x165 MHz
- Maximum resolutions: 1920 x 1200 (single link), 3840x2400 (dual link)
- DVI Input: (8) DVI-D DL 24 pin female
- DVI Output: (1) DVI-D DL 24 pin female
- Audio Input: (8) 3.5mm mini-stereo jack
- Audio Output: (1) 3.5mm mini-stereo jack
- USB Input Connection: (8) Type B
- USB Output Connection: (2) Type A
- Rack Size: 1U (rack-ears included)
- Power Supply: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 4.2"D x 17.1" W x 1.8"H
- Shipping Weight / Unit Weight: 2 lbs. /12 lbs.

FEATURES:

- Supports resolutions up to 3840x2400
- Save time and increase productivity
- Supports all major operating systems - Windows, MacOS and Linux
- Integrated 2-port USB hub
- Front panel switching
- Discrete IR remote (included)
- Discrete switching via integrated RS-232 serial communications
- Supports DDWG standards for DVI monitors
- Rack-mountable

8x
Displays



Computer

