TRMS Digital Multimeter

GREENLEE













- True RMS for no-compromise accuracy when harmonics are present.
- Large LCD for easy viewing.
- AC/DC voltage, AC/DC amperage measurement.
- Non-contact voltage detection for identifying live lines without contacting conductors.
- Easy viewing, backlit display.
- Auto shut-off for longer battery life.
- Low battery indicator.
- Resistance measurement.
- Audible continuity and diode tests.
- Frequency measurement.
- Capacitance measurement.
- Data hold to capture measurement.
- 6000-count LCD for high resolution.
- Min/Max feature for added versatility.
- Audible input alert warns user if leads are in incorrect position.

• Lifetime Limited CAT. NO.	UPC NO.	DESCRIPTION		
DM-350	11871	DMM, 1000V 10A RMS BL		
DM-350-C*	22897*	DMM, 1000V 10A RMS BL		
TSG-3	12034 🚯	Sure-Grip Test Leads		
* Includes Certificate of Calibration Note: See page 358 for replacement case				
CDECIEICATIONS				

SPECIFICATIONS

Amperage Measurement	600.0, 2000 μA; 6.000, 10.00 A
Voltage Measurement	600.0 mV; 6.000, 60.00, 600.0, 1000V
Resistance Measurement	$600.0 \ \Omega; 6.000, 60.00, 600.0 \ kΩ; 6.000, 60.00 \ MΩ$
Frequency Measurement	40 Hz minimum, 100 Hz to 60 kHz maximum, depending on function and range
Capacitance	600.0 nF; 6.000, 60.00, 600.0, 2000 μF
Display	6000-count LCD
Measurement Category	CAT IV, 600V; CAT III, 1000V

TRMS Digital Multimeter













- Large LCD for easy viewing.
- AC/DC voltage, AC/DC amperage measurement.
- Non-contact voltage detection for identifying live lines without contacting conductors.
- · Auto shut-off for longer battery life.
- Low battery indicator.
- Resistance measurement.
- Audible continuity and diode tests.
- Frequency measurement.
- Capacitance measurement.
- Data hold to capture measurement.
- 6000-count LCD for high resolution.
- Min/Max feature for added versatility.
- Audible input alert warns user if leads are in incorrect position.
- Lifetime Limited Warranty.

CAT. NO.	UPC NO.	DESCRIPTION		
DM-330	11870	DMM, 1000V 10A RMS		
DM-330-C*	22895*	DMM, 1000V 10A RMS		
TSG-3	12034 🚯	Sure-Grip Test Leads		
* Includes Certificate of Calibration Note: See page 358 for replacement case				

SPECIFICATIONS

Amperage Measurement	6.000, 10.00 A
Voltage Measurement	600.0 mV; 6.000, 60.00, 600.0, 1000V
Resistance Measurement	600.0 Ω; 6.000 , 60.00 , 600.0 kΩ; 6.000 , 60.00 MΩ
Frequency Measurement	40 Hz minimum, 100 Hz to 60 kHz maximum, depending on function and range
Capacitance	600.0 nF; 6.000, 60.00, 600.0, 2000 μF
Display	6000-count LCD
Measurement Category	CAT IV, 600V; CAT III, 1000V



