



The Intelix DIGI-VGASD-T4 distribution balun sends a single VGA video and stereo audio source to four remote destinations over inexpensive twisted pair cable. In addition, the unit extends RS232 or IR control signals over the same cable.

When used with a compatible Intelix receive balun, the DIGI-VGASD-T4 features 1600x1200 VGA video performance, high-fidelity 20Hz to 20kHz audio performance, and IR or bi-directional RS232 extension up to 350 feet. The unit features local monitor support and is linkable for additional remote destinations.

The Intelix **DigiCat** Series of baluns is the ideal solution for sending high-performance audio and video signals over structured cabling. **When signal quality matters, choose Intelix.**

Technical Specifications

Connectors	One female HD15 output, one female HD15 input, one 1/8" mini audio output, one 1/8" mini audio input, one 1/8" mini IR connection, one female DB9 RS232 connection, four RJ45 outputs, one DIN mini power connector	Temperature	<i>Operating:</i> 32 to 131 F (0 to 55 C) <i>Storage:</i> -4 to 185 F (-20 to 85 C) <i>Humidity:</i> up to 95%
Included Accessories	One (1) 5VDC power supply	Control	IR or RS232; IR takes precedence when both are connected
Maximum Distance*	350 feet	Unshielded Twisted Pair Cabling Specifications (24 gauge or lower solid copper)	Maximum capacitance: 20 pf/foot Impedance: 100 ohms @ 1 MHz Attenuation: 6.6 dB/1000 ft. @ 1 MHz <i>Cat 5, Cat 5e, Cat 6, Cat 7 compatible</i>
Maximum Resolution	1600x1200	Status	Front panel power LED
Video Bandwidth	300 MHz	Max Recommended Links	6 units
Audio Frequency Response	20 Hz to 20 kHz +/- 1dB	Max Distance of AV Cables	6 feet
Crosstalk	-57 dB @ 2 kHz with a +7 dB input -50 dB @ 20 kHz with a +7 dB input	Dimensions	1.19" x 8.88" x 4.75"
Signal to Noise Ratio	70 dB at 7 dBu	Shipping Weight	5.0 lbs
Clipping	7 dBu	Power	5 VDC @ 1.6A
Noise Floor	63 dBu (70 dBu - 7 dBu)	Compatible Receive Baluns	DIGI-VGASD-WP-R DIGI-VGASD-R DIGI-V3SD-R DIGI-V3A2-R
Distortion	<0.08%	Ordering Information	DIGI-VGASD-T4
Enclosure	Metal	Warranty	Two years
HD Compatibility	480p, 720p, 1080i		

Note

When distributing IR, Intelix SD Series technology requires *DIGI-VGASD-IREYE* receivers and *DIGI-VGASD-IREMT* emitters.

*Distances, picture and audio quality may be affected by cable grade, cable quality, source and destination equipment, RF and electrical interference, and cable patches. Intelix specifications are based on straight-through cabling with standard-grade Cat 5.

DigiCat
Series



www.intelix.com

intelix
DESIGN WITH INTELLIGENCE

2222 Pleasant View Road
Suite #1
Middleton, WI 53562

Phone: 608-831-0880
Toll-Free: 1-866-4-MATMIX
Fax: 608-831-1833