

USB EXTENDERS

EXT-USB-200



USB 200 EXTENDER (USB 1.1)

Extends any USB 1.1 signal up to 330 feet (100 meters) with built-in 2 port hub over one CAT-5e cable



FEATURES:

- Operate USB 1.1 peripherals up to 300ft (100m) away from a computer
- CAT-5e cable used for extension
- Integrated 2-port hub at the receiving end
- Plug and play - installs in minutes
- Supports all major operating systems - Windows, MacOS and Linux
- No power supply required at the receiving end
- Supports full 12 Mbps USB standard bandwidth

SPECIFICATIONS :

- USB device support: Full-speed 12 Mbps Low-speed 1.5 Mbps
- USB Input Connector: (1) Type B
- USB Output Connectors: (2) Type A
- Link Connector: (1) RJ-45 shielded
- Power Supply: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 4.2"D x 1.2" W x 1.2"H
- Shipping Weight / Unit Weight: 2 lbs. /1 lb

EXT-USB-400FO



USB 400 FO EXTENDER (USB 2.0)

Extends any USB 2.0 signal up to 1640 feet (500 meters) with built-in 4 port hub over 2-strand LC fiber optic cables



FEATURES:

- Operate USB 2.0 peripherals up to 1640ft (500m) away from a computer
- Integrated 4-port hub at the receiving end
- Provides support for both low-speed and high-speed USB devices
- Fully compliant with USB 2.0 specification as certified by the USB Implementer's Forum
- Supports all major operating systems - Windows, MacOS and Linux.
- Uses 2-strands of multimode LC terminated fiber optic cables.

SPECIFICATIONS :

- USB device support: 480Mbps
- USB Input Connectors: (1) Type B
- USB Output Connectors: (4) Type A
- Link Connector: (2) LC Strand
- Power Supply: 5V DC
- Power Consumption: 15 Watts (max)
- Dimensions(S): 3.2"D x 4.2" W x 1.2"H
- Dimensions(R): 4.2"D x 4.5" W x 1.2"H
- Shipping Weight / Unit Weight: 4 lbs. /1 lb

EXT-USB2.0-LR



USB 2.0 LR EXTENDER

Extends any USB 2.0 signal up to 330 feet (100 meters) away over one CAT-5e cable



FEATURES:

- Operate USB 2.0 peripherals up to 330ft (100m) away from a computer
- Supports low and high-speed USB standards
- Uses industry-standard CAT-5, CAT-5e or CAT-6 cable
- Supports all major operating systems - Windows, MacOS and Linux.
- True plug-and-play, 100% hardware solution with no drivers required
- Operates at full 480 Mbps speed when running in USB 2.0 mode
- Receiver supports up to 2 USB powered connections at 500 mA each

SPECIFICATIONS :

- USB 2.0 Speed: 480 Mbps
- Link Connectors: (1) RJ-45 Shielded
- USB Connectors: Transmitter: (1) USB type B
- USB Connectors: Receiver: (2) USB type A
- Two 500 mA DC powered USB ports at Receiver
- Operating Temperature: 0-70° C
- Power Consumption: 10 Watts (max)
- Power Supply: External 5V DC
- Dimensions: 1.5"D x 3.4" W x 1.1"H
- Shipping Weight / Unit Weight: 2 lbs. /1 lb