

600A AC/DC True RMS Clamp Meter



- True RMS for the most accurate measurement when harmonics are present
- AC/DC amperage, AC/DC voltage, frequency and resistance measuring capability.
- Dual Hall sensor for DC amperage accuracy.
- Easy-to-read backlit display for use in low light conditions.
- Peak and data hold to capture measurement.
- MIN/MAX feature for added versatility.
- Analog bar graph to view quick changes.
- Auto zero for DCA measurement.
- Selectable Auto Off for longer battery life.
- Accessories included: (1) 9V battery, test leads, carrying case.
- Lifetime Limited Warranty.

| CAT. NO. | UPC NO. | DESCRIPTION | | |
|--|-----------|----------------------------|--|--|
| CM-950 | 07700 | AC/DC True RMS Clamp Meter | | |
| CM-950-C* | 10859* | AC/DC True RMS Clamp Meter | | |
| TLK-1 | 12035 🚯 | Test Leads | | |
| Includes Certificate of Calibration Note: See page 358 for replacement case | | | | |
| SPECIFICATIONS | | | | |
| Amperage Measur | rement 40 | 0.0, 600A | | |
| Voltage Measure | ment 40 | 0.0, 600V | | |
| Resistance | 40 | 0.0Ω | | |
| Frequency | 0.4 | 400kHz | | |
| Display | 40 | 00-count LCD | | |
| Jaw Opening | 1.3 | 38" (35 mm) | | |

600A AC/DC Clamp Meter



- AC/DC amperage, AC/DC voltage, frequency and resistance measuring capability.
- Dual Hall sensor for DC amperage accuracy.

Measurement Category CAT III, 600V

- · Easy-to-read backlit display for use in low light conditions.
- · Peak and data hold to capture measurement.
- MIN/MAX feature for added versatility.
- Analog bar graph to view quick changes.
- Auto zero for DCA measurement.
- Selectable Auto Off for longer battery life.
- Accessories included: (1) 9V battery, test leads, carrying case.

CAT III, 600V

• Lifetime Limited Warranty.

Measurement Category

| CAT. NO. | UPC NO. | DESCRIPTION |
|---|-----------------|----------------------------|
| CM-900 | 07699 | AC/DC Clamp Meter |
| CM-900-C* | 10858* | AC/DC Clamp Meter |
| TLK-1 | 12035 🚯 | Test Leads |
| Note: See page 358 for l | epiacement case | |
| SPECIFICATIO | INS | |
| | INS | 400.0, 600A |
| SPECIFICATIO | NS asurement | 400.0, 600A 400.0, 600V |
| SPECIFICATIO Amperage Me | NS asurement | |
| SPECIFICATIO Amperage Me Voltage Meas | NS asurement | 400.0, 600V |
| SPECIFICATIO Amperage Me Voltage Meas Resistance | NS asurement | 400.0, 600V 400.0Ω |

LIFETIM

USA