

ANALOG EXTENDERS

EXT-VGARS232-141



VGA RS-232 EXTENDER

Extends any VGA and RS-232 signal up to 330 feet (100 meters) over one CAT-5e cable



FEATURES:

- Extends any VGA and RS-232C signal up to 330 feet (100 meters)
- Trim pot and DIP switch adjustments for video equalization
- Perfect for digital signage applications
- One CAT-5e cable for extension
- Supports resolutions up to 1080p, 2K, and 1920 x 1200

SPECIFICATIONS:

- Maximum Video Bandwidth: 350 MHz
- Input Video Signal: 1.2 Volts p-p / Input Sync Signal: 5 Volts p-p (TTL)
- Video In: (1) HD-15 male
- Video out: (1) HD-15 female
- RS-232 Input Connector: (1) DB-9 female
- RS-232 Output Connector: (1) DB-9 male
- Link Connector: (1) RJ-45 shielded
- Conforms to RS-232C standards
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 3"D x 4" W x 1.2"H
- Shipping Weight / Unit Weight: 4 lbs. /1 lb

EXT-VGA-AUDIO-141



VGA AUDIO EXTENDER

Extends any VGA signal with analog audio up to 330 feet (100 meters) over one CAT-5e cable



FEATURES:

- Extends any VGA signal with analog audio up to 330 feet (100 meters)
- Trim pot and dip switch adjustment for video equalization
- Perfect for digital signage applications
- One CAT-5e cable for extension
- Supports resolutions up to 1080p, 2K, and 1920 x 1200
- Bi-directional audio transmission for speaker and microphone

SPECIFICATIONS:

- Maximum Video Bandwidth: 350 MHz
- Input Video Signal: 1.2 Volts p-p / Input Sync Signal: 5 Volts p-p (TTL)
- Video In: (1) HD-15 male
- Video out: (1) HD-15 female
- Sample Rate: 5 kHz (min) - 48 kHz (max)
- Frequency Response: 20Hz - 20kHz
- Audio Connector: (1) 3.5mm mini-stereo jack
- Link Connector: (1) RJ-45 shielded
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 2.8"D x 4.7" W x 1.1"H
- Shipping Weight / Unit Weight: 4 lbs. /1 lb

EXT-VGA-CAT5-142



VGA EXTENDER/SPLITTER

Extend any VGA signal up to 1000 feet (300 meters) with VGA distribution to two outputs, all over one CAT-5e cable



FEATURES:

- Extends any VGA signal up to 1000 feet (300 meters)
- One CAT-5e cable for extension
- Trim pot and dip switch adjustment for video equalization
- Supports resolutions up to 1080p, 2K, and 1920 x 1200
- Splits the VGA signal to 2 outputs at the receiver

SPECIFICATIONS:

- Maximum Video Bandwidth: 350 MHz
- Input Video Signal: 1.2 Volts p-p
- Input Sync Signal: 5 Volts p-p (TTL)
- Video In: (1) HD-15 male
- Video out: (2) HD-15 female
- Link Connector: (1) RJ-45 shielded
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions(S): 1.3"D x 3.8" W x 1.1"H
- Dimensions(R): 2.8"D x 4.7" W x 1.1"H
- Shipping Weight / Unit Weight: 2 lbs. /1 lb