



RS-232 EXTENDER

Extends any RS-232 signal up to 1000 feet (300 meters) over one CAT-5e cable

FEATURES:

- Extends any RS-232 compliant device up to 1000 feet (300 meters) from the computer
- Extends all 9 pins for full RS-232 compatibility
- Uses one CAT-5e cable for extension
- Perfect for digital signage applications

SPECIFICATIONS:

- RS-232 Input Connector: (1) DB-9 female
- RS-232 Output Connector: (1) DB-9 male
- Link Connector: (1) RJ-45 shielded
- Conforms to RS-232C standards
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 1.3"D x 3.7" W x .8"H
- Shipping Weight / Unit Weight: 1 lb/1 lb



DIGITAL AUDIO EXTENDER

Extends any S/PDIF or TOSLINK digital audio signal up to 330 feet (100 meters) over one CAT-5e cable

FEATURES:

- Extends any S/PDIF and TOSLINK digital audio signal up to 330 feet (100 meters) from the source
- Supports up to 2-channels of LPCM audio (up to 96 kHz)
- Supports digital bitstream protocols such as DTS and Dolby Digital
- Streamlines audio installations by allowing source devices to be located off-site
- One CAT-5e cable used for extension
- S/PDIF and TOSLINK outputs are active regardless of the input type

SPECIFICATIONS :

- Data Transmission Rate: 12.8 Mbps
- Input: (1) Coaxial (S/PDIF) and (1) Optical (TOSLINK)
- Output: (1) Coaxial (S/PDIF) and (1) Optical (TOSLINK)
- Link Connector: (1) RJ-45 shielded
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 1.4"D x 3.8" W x 1.2"H
- Shipping Weight / Unit Weight: 1 lb/1 lb



AUDIO EXTENDER

Extends analog audio and microphone input up to 1000 feet (300 meters) away from a computer over one CAT-5e cable.

FEATURES:

- Extends any unbalanced line level analog audio device up to 1000 feet (300 meters) from the source to the receiver
- Extends any unbalanced line level analog audio device up to 1000 feet (300 meters) from the receiver to the source
- One CAT-5e cable used for extension
- Bi-directional transmission for speaker and microphone connections

SPECIFICATIONS:

- Sample Rate: 5 kHz (min) - 48 kHz (max)
- Frequency Response: 20Hz - 20kHz
- Audio Connectors: 3.5mm mini-stereo jack
- Link Connector: (1) RJ-45 shielded
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 1.3"D x 3.7" W x .8"H
- Shipping Weight / Unit Weight: 1 lb/1 lb

