

8x4 MATRIX FOR HDMI

Switch a total of eight HDMI signals to any four HDMI outputs



FEATURES:

- Distribute any of the four switched inputs (total of eight inputs) to any combination of the four HDMI outputs
- Supports resolutions up to 1080p/60, 2K and 1920x1200
- Serial RS-232 remote port for switching via control automation
- Discrete IR remote (included)
- Discrete switching via integrated RS-232 serial communications
- Rack-mountable
- HDMI 1.2 compliant/HDMI 1.3 compatible
- HDCP compliant

SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz
- Input Video Signal: 1.2 Volts p-p
- Input DDC Signal: 5 Volts p-p (TTL)
- Maximum Resolution: 1080p/60, 1920x1200
- HDMI Input: (8) Type A 19 pin female
- HDMI Output: (4) Type A 19 pin female
- Remote Control Port: (1) DB-9; RS-232 serial communication
- IR Extension Port: (1) 3.5mm mini-stereo jack
- Rack Size: 1U (rack-ears included)
- Power Supply: 24V DC
- Power Consumption: 60 Watts (max)
- Dimensions: 6.5"D x 17.1" W x 1.8"H
- Shipping Weight / Unit Weight: 9 lbs. /2 lbs.



EXT-HDMI-844

8X8 MATRIX FOR HDMI

Route eight HDMI signals to any eight outputs in any combination



Features:

- Supports resolutions up to 1080p/60, 2K and 1920x1200
- Long-distance remote control at distances of up to 1000 feet optional using wired CAT5 cabled remote
- Discrete IR remote (included)
- Discrete switching via integrated RS-232 serial communications
- Rack-mountable
- HDMI 1.2 compliant/HDMI 1.3 compatible
- HDCP compliant (Only on a one output to one input basis)

SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz
- Input Video Signal: 1.2 Volts p-p
- Maximum Resolution: 1080p/60, 1920x1200
- Remote Control Ports: One RS232 female, One mini-stereo
- HDMI Input: (8) Type A 19 pin female
- HDMI Output: (8) Type A 19 pin female
- Rack Size: 2U (rack-ears included)
- Power Supply: 24V DC
- Power Consumption: 60 Watts (max)
- Dimensions: 7.1"D x 17.1" W x 3.5"H
- Shipping Weight / Unit Weight: 10 lbs. /5 lbs.



EXT-HDMI-848

8X8 DVI MATRIX

Switches eight DVI computers to any eight DVI displays



FEATURES:

- Increases your productivity by providing you with access to eight computers from twelve workstations
- Maintains beautiful, sharp HDTV resolutions up to 1080p, 2K, and 1920x1200
- Discrete IR remote control (included)
- Long-distance remote control at distances of up to 1000 feet optional using wired CAT5 cabled remotes
- Serial RS232 port for remote control via computer or a control automation device such as Crestron
- Supports DDWG standards for DVI monitors
- Not HDCP compliant; for computers only.

SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz
- Maximum Resolution: 1080p (HDTV) / 1920x1200 (PC)
- Input Video Signal: 1.2 Volts p-p
- Input DDC Signal: 5 Volts p-p (TTL)
- Remote Control Ports: One RS232 female, One mini-stereo
- Rack mountable: 2U rack space, rack ears included
- DVI Connector: DVI-I 29 Pin Female (digital only)
- Power Supply: 24V DC
- Power Consumption: 60 Watts (max)
- Dimensions: 7.1"W x 3.5" H x 7.2" D
- Shipping Weight / Unit Weight: 9 lbs. /4 lbs.



EXT-DVI-848