

DVI TO VGA CONVERTER

Converts DVI-D signals to analog VGA



EXT-DVI-2-VGA

FEATURES:

- Supports resolutions up to 1920x1200/60Hz
- Default EDID of 1600x1200; custom resolutions available
- Supports DDWG standard for DVI monitors

SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz (DVI)
- Maximum Video Bandwidth: 350 MHz (VGA)
- Input Video Signal: 1.2 Volts p-p
- Input DDC Signal: 5 Volts p-p (TTL)
- DVI Connector: (1) DVI-I 29 pin female
- VGA Connector: (1) HD-15 VGA female
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 2.7"D x 4.5" W x 1.1"H
- Shipping Weight / Unit Weight: 2 lbs. /1 lb



VGA display



DVI-D source

COMPONENT WITH DIGITAL AUDIO TO HDMI ADAPTER

Converts a component video with a digital audio signal to HDMI

FEATURES:

- Supports resolutions up to 1080p/60 and 1920x1200
- Allows you to connect YPbPr sources to HDMI equipment
- Encodes digital audio with the video signal into HDMI
- Plug-and-play installation
- HDMI 1.2 compliant



SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz (HDMI)
- Maximum Video Bandwidth: 350 MHz (YPbPr)
- Input Video Signal: 1.2 Volts p-p
- HDMI Output Connector: (1) Type A 19 pin female
- Component Connector: (1) YPbPr - 3 RCA
- Audio Input Connectors: (1) Coaxial (S/PDIF)
(1) Optical (TOSLINK)
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 3.7"D x 4" W x 1.2"H
- Shipping Weight / Unit Weight: 2 lbs. /1 lb



Display



Source

EXT-COMPAUD-2-HDMI

COMPONENT WITH AUDIO TO HDMI ADAPTER

Converts a component video with an analog audio signal to HDMI

FEATURES:

- Supports resolutions up to 1080p/60 and 1920x1200
- Allows you to connect YPbPr sources to HDMI equipment
- Encodes analog audio with the video signal into HDMI
- Plug-and-play installation
- HDMI 1.2 compliant



SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz (HDMI)
- Maximum Video Bandwidth: 350 MHz (YPbPr)
- Input Video Signal: 1.2 Volts p-p
- HDMI Output Connector: (1) Type A 19 pin female
- Component Connector: (1) YPbPr - 3 RCA
- Audio Input Connectors: (1) L+R Analog RCA
- Power Supply: 5V DC
- Power Consumption: 5 Watts (max)
- Dimensions: 3.7"D x 4" W x 1.2"H
- Shipping Weight / Unit Weight: 2 lbs. /1 lb



Display



Source

EXT-COMPAUD-2-HDMI