

HDMI OVER RGBS/RGBHV EXTENDER

Extends an HDMI 1.3 signal up to 150 feet (45 meters) over five BNC cables (RGBHV)

EXT-HDMI-5BNC

Features:

- Extends an HDMI 1.3 signal up to 150 ft (45 m) at 1080p
- Replaces existing RGBHV analog projector installations with HDMI
- Supports resolutions up to 1080p, 2K, and 1920 x 1200
- Digital transmission of audio and video over the BNC cables for zero signal loss
- HDMI 1.3 compliant
- HDCP compliant

SPECIFICATIONS:

- Maximum Pixel Clock: 340 MHz
- Maximum Resolution: 1080p/60, 1920x1200
- Input Video Signal: 1.2 Volts p-p
- Input DDC Signal: 5 Volts p-p (TTL)
- HDMI Connector: Type A 19 pin female
- Link Connector: (5) BNC female
- Power Supply: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 3.9" D x 4.25" W x 1.25" H inches
- Shipping Weight / Unit Weight: 3 lbs. /1 lb



HDMI CAT-5 IR EXTENDER MS

Extends an HDMI signal up to 300 feet (90 meters) with return IR repeating over two CAT-5e cables

EXT-HDMIIR-CAT5

Features:

- Extends an HDMI signal up to 150 ft (45 m) at 1080p
- Extends an HDMI signal up to 300 ft (100 m) at 1080i /720p
- Carries IR signals from the viewing environment to the equipment rack
- Small and compact, easy to install
- Improved compensation for cable skew
- A/V signals are sent digitally over CAT-5 cable for zero signal loss
- HDMI 1.2 compliant / HDMI 1.3 compatible
- HDMI/HDCP Compliant

SPECIFICATIONS:

- Maximum Resolution: 1080p/60, 1920x1200
- Input Video Signal: 1.2V p-p
- Input DDC Signal: 5V p-p (TTL)
- HDMI Connector: Type A 19 pin female
- Link Connector: (2) RJ-45 Shielded
- IR blaster jack: 3.5 mm mini-stereo
- Power Supply: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 3.8" D x 4.9" W x 1.25" H
- Shipping Weight / Unit Weight: 4 lbs. /1 lb



HDMI RS-232 EXTENDER MS

Extends an HDMI and RS-232 signal up to 300 feet (90 meters) with IR repeating over two CAT-5e cables

EXT-HDMI RS232-CAT5

Features:

- Extends an HDMI signal up to 150 ft (45 m) at 1080p
- Extends an HDMI signal up to 300 ft (100 m) at 1080i /720p
- Improved compensation for cable skew
- Eliminates equipment noise in the viewing environment
- Supports resolutions up to 1080p, 2K, and 1920 x 1200
- Digital transmission of audio and video over CAT-5e cable for zero signal loss
- HDMI 1.2 compliant / HDMI 1.3 compatible
- HDMI and HDCP compliant
- Serial RS-232 remote port

SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz
- Maximum Res: 1080p/60, 1920x1200
- Input Video Signal: 1.2 Volts p-p
- Input DDC Signal: 5 Volts p-p (TTL)
- HDMI Connector: Type A 19 pin female
- Link Connector: (2) RJ-45 shielded
- IR blaster jack: 3.5 mm mini-stereo
- RS-232 Input: DB-9 female
- RS-232 Output: DB-9 male
- IR support: RC5
- Power Supply: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 3.2" D x 4.9" W x 1.25" H
- Shipping Weight / Unit Weight: 4 lbs. /1 lb

