



lucid 88192: 8-channel 192 kHz A/D and D/A Multi-format Converter



Features

- Double rack space, eight (8) channel, analog to digital / digital to analog, multi-format converter. Applications: Studio, Broadcast, Post-Production.
- Sample rates up to 192 kHz with 24-bit audio conversion.
- Eight (8) channels of AES/EBU and eight (8) channels of SMUX²ADAT digital audio.
- Straightforward setup and operation via front panel encoder and display.
- Real-time metering and XLR analog and AES connectors. (No D-sub breakout snakes required.)

Compatible Products

- GENx192
- XLR to Euroblock Adapters

Certifications

- UL 60065, cUL 60065, IEC 60065, RoHS

Shipping Weight

- 17 lbs. (7.71 kg)

Box Dimensions

- WDH: 24 in x 16 in x 6 in (60.96 cm x 40.64 cm x 15.24 cm)

Retail
(MSRP)

\$3,359

lucid GENx192: Ultra Low Jitter Studio Master Clock



Features

- Single rack space ultra low jitter studio master clock. Applications: Studio, Broadcast, Post-Production, Live Sound.
- Eight (8) Word Clock, four (4) AES clock, and two (2) S/PDIF outputs; Word Clock and AES clock inputs.
- Simultaneously generate/distribute multiple sample rates between the two output banks.
- Generate 44.1-192 kHz, distribute 28-216 kHz.
- TS-75: Automatic Word Clock termination sensing and indication.

Compatible Products

- 88192
- 2x

Certifications

- UL 60065, cUL 60065, IEC 60065, RoHS

Shipping Weight

- 9.5 lbs. (4.31 kg)

Box Dimensions

- WDH: 24 in x 16 in x 4 in (60.96 cm x 40.64 cm x 10.16 cm)

Retail
(MSRP)

\$965

Symetrix, Inc.

6408 216th Street SW

Mountlake Terrace, WA 98043 USA

T +1.425.778.7728 F +1.425.778.7727

www.SymetrixAudio.com