DIGI-HDMI-4X4 Twisted Pair Matrix Switcher

Technical Specifications

The Intelix DIGI-HDMI-4X4 combines professional-grade performance with comprehensive control options, providing an easy-to-use, flexible, and powerful solution for high-definition audio/video distribution applications. A true matrix switcher, the DIGI-HDMI-4X4 features Four HDMI inputs four HDMI inputs, four HDMI outputs and four twisted pair extender outputs. The matrix supports 1080i and 1080p high-definition video and is HDMI 1.3b compliant. Switching is controlled via a diagnostic front panel interface or remotely via RS232, IR, or Ethernet.

In addition, the DIGI-HDMI-4X4 features four pass-through IR channels which distribute remote IR commands from in-room controllers, through compatible Intelix twisted pair extenders, up to 150 feet over twisted pair cable, and out of the matrix, thereby allowing complete control of remote sources from the destination.



Features

Four HDMI outputs and four twisted pair balun outputs

1080i and 1080p compatible

HDMI 1.3b and HDCP compliant

Distributes four IR signals from remote destinations to local sources

Front panel, Ethernet, RS232 and IR control


Included wireless remote


Rack-mountable

Specifications

Vertical Frequency Range 24 - 60 Hz **Operating Temperature Range** -41 to 95 degrees F -5 to 35 degrees C **Output Video** HDMI 1.2/HDMI 1.3 **Operating Humidity Range** 5 to 90% RH non-condensing Signaling Rate 2.25 gigabits per second Front panel channel, RS232, IR, Control **Input DDC Signal** 5.0 volts p-p (TTL) and Ethernet Input Video Signal 0.5 to 1.0 volts p-p **Enclosure** Black metal Video Amplifier Bandwidth 255 MHz **Max Power Consumption** 11 watts **Input Connectors** Four (4) HDMI type A connectors **Power** 5 VDC Four (4) HDMI type A connectors with **Output Connectors** CE, RoHS Regulatory locking screws Shipping Weight 7.1 lbs Four (4) dual twisted pair connectors **Intelix Part Number** DIGI-HDMI-4X4 **Supported Video Resolutions** 480i, 480p, 576i, 576p, 720p, 1080i, 1080p 8, 10, 12 bits per channel **Included Accessories** One (1) 5 VDC power supply Two (2) 19" rack mounting ears Dolby TrueHD 7.1, Dolby TrueHD 5.1, Supported Audio Dolby Digital 5.1, DTS-HD Master One (1) wireless remote control Audio 7.1, DTS-HD Master Audio 5.1, **Compatible Intelix** DIGI-HDMI-HR-R DTS 5.1, PCM 2.0, PCM 5.1 **Twisted Pair Receivers** DIGI-HDMI-IR-R 17.375" x 8.375" x 1.625" **Dimensions Rack-mounting** 1 RU **Diagnostic Indicators** Front panel input to output LEDs Warranty 2 years Front panel keylock LED $C \in$

































www.intelix.com

2222 Pleasant View Road Suite #1 Middleton, WI 53562

Phone: 608-831-0880 Toll-Free: 1-866-4-MATMIX Fax: 608-831-1833