

## 6" ABS Plastic 20 Watt Amplified Weatherproof P.A. Speaker

- 3-16 Ohms input impedance
- 20W max. output audio
- 8 Ohms speaker impedance
- Requires a 10-16V DC power supply
- 2 A, 3AG fuse
- 500-5 kHz frequency response



**ASPC20**

## Strobe Flasher

- 6 - 12V DC
- Weatherproof
- Base 3.75" D x 1.75" H
- Designed for intermittent use only



Blue **SFB12**  
 Red **SFR12**  
 Amber **SFA12**

## 12V DC 4 AMP Reg. Filtered Power Supply With 5 AMP Surge & Cigarette Lighter Adapter Built-In Front Panel



- Input: 117V AC 60 Hz
- Output: 12V DC 4 amp constant, 5 amp surge
- 7.5" L x 4.25" W x 2.6" H
- 4 lbs.

**PSR4C**

## 70/25 Volt Volume Controls



**Decorative Style Units do not include outer wall plate**

### 70/25 Volt Decorative Style Volume Controls & Accessories

- DVC1070** 10 Watt, 70 Volt, 10 Step Volume Control/Attenuator  
**DVC2570** 25 Watt, 70 Volt, 10 Step Volume Control/Attenuator



**WAT10W**



**WAT50**

### 70/25 Volt Wall Plate Volume Controls

Part #	Sound	Wattage	Output	Knob/Plate Color
<b>WAT10</b>	Mono	10	70/25V	Silver
<b>WAT10W</b>	Mono	10	70/25V	White
<b>WAT50</b>	Mono	50	70/25V	Silver
<b>WAT50W</b>	Mono	50	70/25V	White

*Units with "W" come with white plastic plate & white knob - Units with a silver plate come with a black knob*

**8Ω Volume Controls found on page 56**