



## **MX-880Z Remote Control**

**Wand-style, IR/ZigBee RF, PC Programmable Color LCD remote control.**

- ZigBee RF technology and unlimited addressing enable any number of simultaneous users in MDU installations
- Fast, simple PC programming software includes URC's extensive IR database
- Powerful customization and labeling for up to 48 devices (8 pages each)
- Advanced IF/Else logic enables tracking of power status, users, etc.
- Motion sensor detects movement and activates backlighting feature

## **MRZ-260 Base Station**

**ZigBee RF to IR base station.**

- Addressable ZigBee RF Base Station with integrated antenna
- Four independent IR Engines in one MRZ-260 (as if there are 4 base stations in one!)
- Enables up to four MX-880Z's to simultaneously control four IR components connected to one MRZ-260
- Built-in front panel IR blaster
- Includes mounting bracket and power supply



## **RFTX-1 Antenna Module**

**Narrow Band transmitter for IP or ZigBee base stations.**

- Controls URC Lighting Control products
- Narrow Band RF transmitter for IP or ZigBee stations (such as MRZ-260)
- RF frequency select switch (418MHz or 433MHz)
- Power and interference (RFI) indicator LEDs
- Includes wall mount and 10' connecting cable



**UNIVERSAL<sup>®</sup>**  
remote control

**The Pioneer in Control Technology**

**COMPLETE<sup>™</sup>**  
**CONTROL**

# Immune to Interference

## MX-880Z Specifications

**Memory:** 32 Megabits of Flash Memory Total (28 Megabits for User Configuration)

**Customization Capability:** Up to 48 devices and up to 8 pages each for a total of 384 pages

**Learning Capability:** Standard frequencies (15kHz to 460kHz)

**Macro Capability:** Up to 255 steps each

**IR Range (Line-of-Sight via Infrared):** 30-50 feet, depending on the environment

**RF Range (Radio Frequency):** 50-100 feet, depending upon the environment

**RF Frequency:** 2.4GHz

**Number of Addresses:** 65,535

**Weight:** 6.9 ounces (with battery loaded)

**Size:** 8" H x 2.25" W x 1.25" D

**Battery:** Lithium Ion rechargeable battery included

## MRZ-260 Specifications

**Power Supply:** 9V 300mA (AC Adapter Included)

**IR Flasher Line Outputs:** 3.5mm Mono Mini Jack

**RF Frequency:** 2.4GHz

**Number of Addresses:** 65,535

## RFTX-1 Specifications

**RF Range (Radio Frequency):** 50-100 feet, depending upon the environment

**RF Frequency:** 418 MHz or 433.92 MHz (User Selectable)

**Weight:** 2.9 ounces

**Size:** 1.5" H x 2.25" W x .45" D



The Pioneer in Control Technology

500 Mamaroneck Avenue  
Harrison, NY 10528  
Phone: (914) 835-4484  
Fax: (914) 835-4532  
[www.universalremote.com](http://www.universalremote.com)