

Speco Technologies' high-end, Ciela Surround™ Sound Series has been engineered for each speaker in the system to provide the ultimate listening experience for use in a surround sound system.



Our in-ceiling (SP6CLC/SP8CLC) and in-wall (SP6CLW/SP8CLW) speakers feature pivoting titanium dome tweeters that focus high frequencies to your customized listening area. The injection-designed woofers with rubber surround deliver powerful and rich low frequency responses with minimal distortion.

Ciela Surround™ Sound Series dual voice coil, in-wall subwoofer (SP8CLSW) offers a deep, rich bass experience without sacrificing floor space in your home theater environment. The in-wall center channel speaker (SP5CLCC) offers an ultra-wide, horizontal sound dispersion that brings pre-recorded dialog to the forefront. The Ciela Surround™ Sound Series with its sonic performance and flat frequency response curves, will provide you with crystal clear sound for your home theater.



## 6.5" And 8.5" In-Ceiling Speaker System

- 6.5" Injection Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 60 Watts RMS/ 100 Watts Max
- Frequency Response: 60Hz-20kHz
- 12 oz. Magnet • 8 Ohms
- 9" Diameter x 4" D
- Mounting Dimension: 8 3/8" Diameter
- dB Switches for Woofer & Tweeter
- EZ mount tabs for ease of installation

- 8" Injection Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 80 Watts RMS/ 120 Watts Max
- Frequency Response: 50Hz-20kHz
- 12 oz. Magnet • 8 Ohms
- 11" Diameter x 5 3/4" D
- Mounting Dimension: 10" Diameter
- dB Switches for Woofer & Tweeter
- EZ mount tabs for ease of installation



Sold in pairs **SP6CLC**  
Mounting Brackets **BRC6F**

Sold in pairs **SP8CLC**  
Mounting Brackets **BRC8L**

## 6.5" And 8.5" In-Wall Speaker System

- 6.5" Injection Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 60 Watts RMS/ 100 Watts Max
- Frequency Response: 60Hz-20kHz
- 12 oz. Magnet • 8 Ohms
- 8 3/4" W x 12 1/4" H x 3 1/2" D
- Mounting Dimensions: 7 1/2" L x 11" H
- dB Switches for Woofer & Tweeter
- EZ mount tabs for ease of installation

- 8" Injection Cone with Rubber Surround
- Titanium Dome Pivoting Tweeter
- 80 Watts RMS/ 120 Watts Max
- Frequency Response: 50Hz-20kHz
- 12 oz. Magnet • 8 Ohms
- 10 1/4" W x 14 1/4" H x 4" D
- Mounting Dimensions: 9" L x 13" H
- dB Switches for Woofer & Tweeter
- EZ mount tabs for ease of installation



Sold in pairs **SP6CLW**  
Mounting Brackets **BRW6F**

Sold in pairs **SP8CLW**  
Mounting Brackets **BRW8L**

## 8" In-Wall Passive Subwoofer

- 8" Polypropylene Woofer with Rubber Surround
- 100 Watts RMS/ 160 Watts Max.
- Frequency Response: 40Hz-140Hz
- 20 oz. Magnet • 8 Ohms
- 10 1/8" W x 10 1/8" H x 4 1/4" D
- Mounting Dimensions: 8 3/4" L x 8 3/4" H
- Dual Voice Coil • EZ mount tabs for ease of installation



Sold individually **SP8CLSW**  
Mounting Bracket **BRW8SW**

## 5.25" Center Channel Speaker

- 5.25" Injection Cones with Rubber Surround
- Titanium Dome Tweeter
- 80 Watts RMS/ 140 Watts Max
- Frequency Response: 65Hz-20kHz
- 8 oz. Shielded Magnets • 8 Ohms
- 17 1/2" W x 8 3/4" H x 3 3/4" D
- Mounting Dimensions: 16 1/2" L x 7 1/2" H



Sold individually **SP5CLCC**