



DSx H.264 CODECS

VIDEO & GRAPHICS OVER IP

DSx SD/HD Video Codec
DSx 200 Graphics Codec

- Encoding or decoding**
- High profile H.264 compression**
- Video and graphics over IP**
- 4 SD video channels**
- 1 HD or graphics channel**
- Power-over-Ethernet**
- Signal monitoring**
- On-screen display**
- Time code**

RGB Spectrum offers DSx™ codecs with advanced H.264 compression. The codecs provide an unmatched combination of outstanding image quality, performance and feature-rich capability, using H.264 high profile compression technology to optimize image quality with maximum bandwidth efficiency.

Two models are offered. The DSx SD/HD codec encodes and streams either a single channel of high definition HD video or four NTSC/PAL video channels simultaneously at up to 30 frames per second each. The DSx 200 codec encodes graphics at up to 1280 x 1024 resolution or HD video at up to 30 fps.

When encoding, the codecs can display a live or encoded image for monitoring. The DSx SD/HD can display any single image or all four arranged in a quad mode.

When decoding, the DSx SD/HD can display one HD stream or four SD streams. Video and graphic streams can also be decoded using commercial off-the-shelf PC software.

An on-screen display (OSD) offers titling and time code. External time code synchronization sources time code from a Network Time Server (NTS/NTP) and inserts it into the video stream. Operation is easy and intuitive using the embedded web-based graphical user interface.


DSx codecs offer a choice of external power or Power-over-Ethernet (PoE). Units are freestanding. A single/dual unit rackmount tray is also available.

The combination of superb image quality, rich feature set, compact size, robust packaging, and 24/7 reliability makes DSx codecs the ideal solution for mission-critical applications.





Specifications

	Order #	DSx SD/HD	DSx 200
Video & Graphics Inputs			
SD Video			
Channels		4	•••
Connector type		BNC	•••
Resolution		720x480, 720x576 interlaced	•••
HD Video			
Channels		1	1
Connector type		HDMI	DVI-I
Resolution		1080p, 1080i, 720p	1080p, 1080i, 720p
Graphics			
Channels		•••	1
Connector type		•••	DVI-I
Resolution		•••	1280x1024, 1024x768, 800x600 @ 60 Hz
Audio Inputs			
SD Analog			
Number		4 mono	•••
Sample rate		Up to 48 kHz	•••
Connector type		Terminal block	•••
Graphics/HD Video			
Number		1 stereo	1 stereo
Sample rate		Up to 48 kHz	Up to 48 kHz
Connector type		HDMI	3.5 mm Audio mini-jack
Encoding/Streaming/Decoding			
Encode/stream format		H.264 High Pro le (Level 4.1), RTSP, Multicast UDP	H.264 High Profile (Level 4.1), RTSP, Multicast UDP
Decode format		H.264	H.264
Bit stream bandwidth		User selectable from 250 Kbps to 10 Mbps	User selectable from 4 Mbps to 10 Mbps
Audio compression		AAC LC (Low Complexity)	AAC LC (Low Complexity)
Resolution		HD, SD @ 30 fps	1280x1024, 1024x768, 800x600, HD, SD @ 30 fps
Decode display		SD: full screen or 4 streams in a 2x2 quad HD: full screen	Full screen
Output & Monitoring			
Format		Unprocessed or processed (encoded/decoded) images	Unprocessed or processed (encoded/decoded) images
SD Video			
Connector type		BNC (single channel); HDMI (quad image)	•••
Resolution		1080i, 720p	•••
Display capability		Input signal loop, display of any single channel full screen (BNC) or a quad image of all four channels (HDMI)	••••
Graphics/HD Video			
Connector type		BNC (single channel); HDMI (quad image)	DVI-D
Display capability		Input signal loop, display of any single channel full screen (BNC) or a quad image of all four channels (HDMI)	Display full screen
Resolution		1080i, 720p	1080i, 720p, 1280x1024, 1024x768, 800x600 @ 60 Hz
External Time Code Synchronization			
Source		Network Time Server	Network Time Server
Format		Network Time Protocol (NTP) embedded time code in video stream	Network Time Protocol (NTP) embedded time code in video stream
Audio Outputs			
SD Analog			
Number		1 mono	•••
Connector type		3.5mm audio mini-jack	•••
SD Analog			
Number		1 stereo	1 stereo
Sample rate		Up to 48 kHz	Up to 48 kHz
Connector type		HDMI	3.5mm audio mini-jack
Graphics/HD			
Number		1 stereo	1 stereo
Sample rate		Up to 48 kHz	Up to 48 kHz
Connector type		HDMI	3.5mm audio mini-jack
Control			
Network connection		10/100/1000 Base-T Ethernet, RJ 45 connector	10/100/1000 Base-T Ethernet, RJ 45 connector
Command line		RS-232, RS-485	RS-232, RS-485
Graphical interface		Internal web server for browser based control software	Internal web server for browser based control software
On screen display (OSD)		Display time code and titling	Display time code and titling
Physical			
Enclosure size		6.6" W x 5.7" D x 1.6" H	6.6" W x 7.3" D x 1.6" H
Weight		3.0 lbs	3.2 lbs
Power		Power over Ethernet (PoE) (802.3af) or external 9 to 40 VDC power supply	Power over Ethernet (PoE) (802.3af) or external 9 to 40 VDC power supply
Rackmount option		Power consumption: <8W (typical) 1 RU tray for mounting 1 or 2 DSx units	Power consumption: <8W (typical) 1 RU tray for mounting 1 or 2 DSx units



DSx SD/HD



DSx 200

