

We've utilized our many years of sound expertise in developing our core in-wall audio line; The Series 25 In-Wall Speaker Line. Manufactured from durable and quality components, they provide an exceptional value. Enjoy the premium performance of full-range sound in your listening environment with these high quality speakers.

Plastic enclosure back box offers extra component protection & consistent sound quality

5.25" In-Wall Enclosed Speaker System

- 5.25" fiberglass woofer
- Titanium swivel dome tweeter
- 55 - 20 kHz. frequency response
- 40 W RMS/80 W max.
- 8 Ohms
- 88 dB sensitivity
- 3.6" L x 8.3" W x 11.75" H
- Cut out dimensions: 10 5/8" x 7" x 3 1/2"
- EZ mount tabs for easy installation



Sold in pairs
SP525BB

6.5" In-Wall Enclosed Speaker System

- 6.5" fiberglass woofer
- Titanium swivel dome tweeter
- 50 - 20 kHz. frequency response
- 60 W RMS/100 W max.
- 8 Ohms
- 88 dB sensitivity
- 4.25" L x 8.6" W x 12" H
- Cut out dimensions: 10 5/8" x 7 5/8" x 4"
- EZ mount tabs for easy installation



Sold in pairs
SP625BB

8" In-Wall Enclosed Speaker System

- 8" fiberglass woofer
- Titanium swivel dome tweeter
- 50 - 20 kHz. frequency response
- 80 W RMS/120 W max.
- 8 Ohms
- 88 dB sensitivity
- 4.1" L x 10" W x 14" H
- Cut out dimensions: 12 6/8" x 8 5/8" x 3 7/8"
- EZ mount tabs for easy installation



Sold in pairs
SP825BB

In-Wall Back Box Items (SP525BB, SP625BB, SP825BB designed to be used without support brackets)

Classic Series In-Ceiling Speakers

2-Way In-Ceiling Enclosed Speaker Systems

Plastic enclosure back box offers extra component protection & consistent sound quality

6.5"

- Polypropylene cone woofer / mylar tweeter
- 35 Watts RMS / 100 Watts maximum
- Sensitivity: 90 dB (1W/1M)
- Frequency range: 65 - 20 kHz.
- 9.5" Dia. x 5.5" D
- Mounting hole size: 8.06" Dia.

SP6ECS Sold in pairs
BRC6F Mounting Brackets

8"

- Polypropylene cone woofer / mylar tweeter
- 35 Watts RMS / 100 Watts maximum
- Sensitivity: 92 dB (1W/1M)
- Frequency range: 50 - 20 kHz.
- 11" Dia. x 7" D
- Mounting hole size: 9.625" Dia.

SP8ECS Sold in pairs
BRC8F Mounting Brackets



2-Way 6.5" Dual Voice Coil Speaker

- Dual Voice Coil
- 6.5" Woven Glass Woofer with Rubber Surround
- Two Silk Dome Tweeters
- 50 Watts RMS/80 Watts Max.
- 60Hz-20kHz
- 8 Ohms

- 10 oz. Magnet
- 9" Dia. x 3.25" D
- Mounting hole size 7.75" Dia.
- EZ mounting tabs

SP652CD Sold individually
BRC6 Mounting Brackets

