Engineered by Symetrix



Symetrix, Inc. Full Line Catalog • February 2010

airlools 6100: Broadcast Audio Delay



ACTION STORMAR FOR A STORMAR F

Features

- HD-compatible 24-bit digital delay unit for live broadcast that prevents unwanted profanity or comments from reaching the airwayes
- Adds RS-232, AES3/EBU, digital audio I/O and TC89 time code integration to the 6000's feature set.
- Up to forty (40) seconds of full bandwidth stereo delay (user programmable in 0.1 second increments).
- User selectable delay algorithms. Tailored for music and speech.
- Remotely controlled from the AirTools RC-6000 or from your custom panel.

Compatible Products

- RC-6000
- XLR to Euroblock Cables

Certifications

■ UL 60065, cUL 60065, IEC 60065, RoHS

9

Shipping Weight

■ 12 lbs. (5.44 kg)

Box Dimensions

■ WDH: 24 in x 16 in x 4 in (60.96 cm x 40.64 cm x 10.16 cm)

Retail (MSRP)

\$3,149

Symetrix, Inc.

6408 216th Street SW

Mountlake Terrace, WA 98043 USA

T +1.425.778.7728 F +1.425.778.7727

www.SymetrixAudio.com

O Symetrix

►SymNet

<u>⊿irloo</u>ls

