

Create the perfect projection horn for your application by pairing our casings with our universal drivers

20" Aluminum Weatherproof Projector Horn For Use With SRD Drivers

Size 20" Dia. x 20.25" L
Dispersion 80°
Low end cutoff 250 Hz



SRH20

16" Aluminum Weatherproof Projector Horn For Use With SRD Drivers

Size 16" Dia x 13.5" L
Dispersion 90°
Low end cutoff 250 Hz



SRH16

15" x 9" Aluminum Weatherproof Projector Horn For Use With SRD Drivers

Size 15" x 9" x 12.75" L
Dispersion 120° x 60°
Low end cutoff 250 Hz



SRH159R

35 Watt RMS Universal Driver With Built-In 70 Volt Line Transformer

Freq. Resp. 250-6 kHz
Transformer taps ... 35, 25, 15, 10,
Power rating 35 W RMS, 45 W Max.
Sensitivity 106 dB
Throat diameter 1.375 x 18 TPI



**Replacement
voice coils available**

SRD35T

50 Watt RMS Universal Driver

Freq. Resp. 250-6 kHz
Impedance 16 Ohms
Power rating 50W RMS, 65W Max.
Sensitivity 110 dB
Throat diameter 1.4 x 18 TPI



**Replacement
voice coils available**

SRD50

75 Watt RMS Universal Driver

Freq. Resp. 250-8 kHz
Impedance 16 Ohms
Power rating 75 W RMS, 90 W Max.
Sensitivity 110 dB
Throat diameter 1.3 x 18 TPI



**Replacement
voice coils available**

SRD75

80 Watt RMS Universal Driver With Built-In 70 Volt Line Transformer

Freq. Resp. 300-5 kHz
Taps 80, 40, 20, 10, 5
Power Rating 80 W RMS, 100 W Max.
Sensitivity 112 dB
Throat diameter 1.375 x 18 TPI



**Replacement
voice coils available**

SRD80T

100 Watt RMS Universal Driver

Freq. Resp. 250-8 kHz
Impedance 16 Ohms
Power rating 100 W RMS, 120 W Max.
Sensitivity 113 dB
Throat diameter 1.3 x 18 TPI



**Replacement
voice coils available**

SRD100