

EZLINX™ TERMINATION SYSTEM

CALL 800-530-8998 TO ORDER

MOLDED BNC CABLES

Terminated with 75-ohm BNC molded connectors and available in 3 and 5 conductors with male or female ends.

Length (in.)	Connection	Part #
20	5 BNC Male to 13-Pin EZLINX Male	EZ-5BNCM
20	5 BNC Female to 13-Pin EZLINX Male	EZ-5BNCF
20	3 BNC Male to 13-Pin EZLINX Male	EZ-3BNCM
20	3 BNC Female to 13-Pin EZLINX Male	EZ-3BNCF
20	3 BNC Male + 2 RCA Male to 13-Pin EZLINX Male	EZ-3BNCM2RCAM

BNC option
EZ-3BNCM2RCAM
shown

MOLDED VGA CABLES

Terminated with molded HD15 hoods with thumbscrews. Compliant with ID bit/DDC communication requirements.

Length (in.)	Connection	Part #
20	HD15 Male to 13-Pin EZLINX Male	EZ-VGAM
20	HD15 Female to 13-Pin EZLINX Male	EZ-VGAF

VGA option
EZ-VGAM
shown

MOLDED ANALOG DVI CABLE

This new Digital Visual Interface (DVI) cable adheres to the industry DVI protocol for your digital video installation. DVI option is analog only.

Length (in.)	Connection	Part #
20	DVI-A Male to 13-Pin EZLINX Male	EZ-DVI/A

ANALOG DVI option
EZ-DVI/A
shown

MOLDED S-VIDEO/RCA CABLE

This cable provides an ideal A/V solution. It includes S-Video and Left/Right Stereo Audio RCAs.

Length (in.)	Connection	Part #
20	2 RCA Male + S-V Male to 13-Pin EZLINX Male	EZ-SVM-L/R

S-VIDEO/RCA option
EZ-SVM-L/R
shown

MOLDED UNTERMINATED CABLES

This customizable solution allows the installer to terminate the cable end in the field with the appropriate connector needed for the job.

Length (in.)	Connection	Part #
20	Unterminated cable end to 13-Pin EZLINX Male	EZ-CUSTOM

When your installation project calls for a specific type of termination style, our customizable solution stands ready to deliver. Let our custom cable assembly area produce the correct termination for your project. Call us today for details.

Specifications Subject to Change. Photos of products not shown actual size. All products are patent pending.

EZ-LINX 5RCAF option
EZ-LINX-CABLE
shown

Every option
attaches in seconds

ORDERING IS FAST & EASY, CALL TODAY!

800-530-8998