

Solid 25 AWG RGBHV Cables

Non-Plenum & Plenum



SOLID 25 AWG RGBHV CABLE - NON-PLENUM

Part#: RGB5C-25-CM	# of Conductors	AWG Center Conductor	NOM Dielectric (Inches)	Shield Construction	NOM Jacket (Inches)	NOM OD (Inches)	NOM Capacitance (pF/ft)	NOM Velocity of Propagation	NOM Attenuation									
									MHz	db/100'								
	5	25 AWG Solid BC	.077 FPE	100% Aluminum Poly 90% 38 AWG TC Spiral Braid	.026	.340	18.0	78%	100	5.10								
									200	7.10								
									400	10.50								
									1000	17.90								
							PERFECT CONNECTOR MATCHES <table border="1"> <thead> <tr> <th>ITEM #</th> <th>PART #</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>CM-RGB25S-BNC</td> </tr> <tr> <td>5</td> <td>CM-RGB25S-RCA</td> </tr> <tr> <td>6</td> <td>CM-RGB25S-GRCA</td> </tr> </tbody> </table>				ITEM #	PART #	4	CM-RGB25S-BNC	5	CM-RGB25S-RCA	6	CM-RGB25S-GRCA
ITEM #	PART #																	
4	CM-RGB25S-BNC																	
5	CM-RGB25S-RCA																	
6	CM-RGB25S-GRCA																	

SOLID 25 AWG RGBHV CABLE - PLENUM

Part#: RGB5C-25-CMP	# of Conductors	AWG Center Conductor	NOM Dielectric (Inches)	Shield Construction	NOM Jacket (Inches)	NOM OD (Inches)	NOM Capacitance (pF/ft)	NOM Velocity of Propagation	NOM Attenuation									
									MHz	db/100'								
	5	25 AWG Solid BC	.074 FFEP	100% Aluminum Poly 98% 38 AWG TC Spiral Braid	.016	.315	16.0	83%	100	5.10								
									200	7.10								
									400	10.50								
									1000	17.90								
							PERFECT CONNECTOR MATCHES <table border="1"> <thead> <tr> <th>ITEM #</th> <th>PART #</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>CM-RGB25S-BNC</td> </tr> <tr> <td>5</td> <td>CM-RGB25S-RCA</td> </tr> <tr> <td>6</td> <td>CM-RGB25S-GRCA</td> </tr> </tbody> </table>				ITEM #	PART #	4	CM-RGB25S-BNC	5	CM-RGB25S-RCA	6	CM-RGB25S-GRCA
ITEM #	PART #																	
4	CM-RGB25S-BNC																	
5	CM-RGB25S-RCA																	
6	CM-RGB25S-GRCA																	

SOLID 25 AWG RGBHV COMPOSITE CABLE - PLENUM

Part#: RGB6C-25/22-2P-CMP	# of Conductors	AWG Center Conductor	NOM Dielectric (Inches)	Shield Construction	NOM Jacket (Inches)	NOM OD (Inches)	NOM Capacitance (pF/ft)	NOM Velocity of Propagation	NOM Attenuation									
									MHz	db/100'								
	6	25 AWG Solid BC	.074 FFEP	100% Aluminum/ Poly Tape + 90% TC Spiral Braid	.010 PL-PVC	.106	16.0	83%	100	5.10								
									200	7.10								
	4 (2 pair)	22 STR TC (7x30)	.007 PL-PVC	100% Foil + 22 AWG TC Drain	.008 PL-PVC	.102				400	10.50							
										1000	17.90							
Overall Construction					.016 PL-PVC	.388												
							PERFECT CONNECTOR MATCHES <table border="1"> <thead> <tr> <th>ITEM #</th> <th>PART #</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>CM-RGB25S-BNC</td> </tr> <tr> <td>5</td> <td>CM-RGB25S-RCA</td> </tr> <tr> <td>6</td> <td>CM-RGB25S-GRCA</td> </tr> </tbody> </table>				ITEM #	PART #	4	CM-RGB25S-BNC	5	CM-RGB25S-RCA	6	CM-RGB25S-GRCA
ITEM #	PART #																	
4	CM-RGB25S-BNC																	
5	CM-RGB25S-RCA																	
6	CM-RGB25S-GRCA																	

ORDER YOUR

SOLID 25 AWG CONNECTORS

4

Part #: CM-RGB25S-BNC

5

Part #: CM-RGB25S-RCA

6

Part #: CM-RGB25S-GRCA

1-PIECE RCA & BNC CONNECTORS!

800-530-8998

PERFORMANCE. SELECTION. VALUE.



ORDER TODAY!



QUICKLINX™ SOLID 25 AWG CABLES